MOVING PICTURE CODING APPARATUS

BACKGROUND OF THE INVENTION

[0001] The present invention relates to a bit rate control method for a moving picture coding apparatus to produce the moving picture data in which the bit rate is different[[,]] from the compression coded moving picture data.

[0002] Recently, according to the development of the digital signal processing engineering, ~~the~~ moving picture data can be compressed and coded, and the ~~compression~~compression and coded moving picture data is ~~easily treated~~easy to handle. Further, with the development of a computer network, the ~~chance to transmit and receive the compression~~compressed and coded moving picture data are increasingly transmitted and received through various transmission paths ~~is increased~~. For example, as a TV broadcasting station, a large amount of the moving picture data previously accumulated, is compression coded and saved, and as a VOD (Video On Demand), at the need of the user, the ~~compression~~compressed and coded moving picture data can be transmitted onto the transmission path.

[0003] ~~However, in the case where the compression coded moving picture data is transmitted onto the transmission path, there is sometimes a case where the bit rate which can be transmitted on the transmission path is different from the bit rate of the moving picture, and in the case where the bit rate of the moving picture data is large, when the moving picture is transmitted as it is, there is a~~

problem that the delay is generated in the reception data, and the moving picture data can not be reproduced in the real time. Accordingly, in order to reproduce a moving picture in the real time, it is necessary that the bit rate of the moving picture is lowered. Further, it is necessary that the bit rate of the moving picture data is adjusted also to the bit rate at which the reception terminal equipment by which the moving picture data is received, can receive. Further, even in the case where not the whole frame in the compression coded moving picture data, but only a portion of the frame is quarried out and transmitted, when the bit rate of the quarried out moving picture data exceeds the bit rate at which the transmission path can transmit, it is necessary that the processing to lower the bit rate is conducted. As described above, when the moving picture data is transmitted through various reception terminal equipments and transmission paths, it is necessary that the bit rate of the moving picture data is changed by adjusting to various bit rates, and by a time period in which it takes for the processing of the rate control, the delay is generated in the data transmission

However, where the compressed and coded moving picture data is transmitted to the transmission path, it is possible that the bit rate which can be transmitted on the transmission path differs from the bit rate of the moving picture. If the bit rate of the moving picture data is high, when the moving picture is transmitted at that rate, there is a problem in that delay is generated in the reception data, and the moving picture data cannot be reproduced in real time. Accordingly, in order to reproduce a moving picture in real time, it is necessary that the bit rate of the

moving picture be reduced. Further, it is necessary that the bit rate of the moving picture data also be adjusted to the receiving bit rate of the terminal equipment receiving the moving picture data. Further, even in the case where not the whole frame in the compressed and coded moving picture data, but only a portion of the frame is selected and removed and transmitted, when the bit rate of the selected and removed moving picture data exceeds the bit rate of the transmission path, processing must be conducted to the reduced bit rate. As described above, when the moving picture data is transmitted through various reception terminal equipment and transmission paths, it is necessary that the bit rate of the moving picture data be changed by adjusting to various bit rates, and a delay is generated in the data transmission by a time period for the processing of the rate control.

[0004] Further, when the VOD server sends out a plurality of moving picture data to a plurality of terminal equipment[[s]], as in the case of the VOD, in proportional to the plurality of number of terminal equipments connected to the VOD server, because the rate control processing becomes heavy, and the burden onto the VOD server becomes large, the number of terminal equipments which can be simultaneously connected, arethe quantity of simultaneous connected terminal equipment is limited. This is because excessive rate control processing is required, burdening the VOD server. That is, the bit rate control method [[to]]that quickly changes the bit rate of the moving picture data is absolutely necessary.

[0005] ~~In such the case, as the conventional technique to control the bit rate of the compression-coded moving picture data, a method in which, initially, the moving picture data is decoded into the non-compression moving picture data, and coded again, and thereby the bit rate is changed, is well known. However, in this method, because the moving picture data is decoded once, and further, coded again, the burden of this processing is large, and there is a problem that it is difficult to quickly change the bit rate and produce the moving picture data~~The conventional and well known technique of controlling the bit rate of compressed and coded moving picture data is to initially decode the data into non-compressed moving picture data and then to code it again, thereby changing the bit rate. However, in this method, excessive processing is required because the moving picture data is decoded and coded again. In addition, it is difficult to quickly change the bit rate and produce the moving picture data.

[0006] Further, as the conventional technique to lighten the re-coding processing and to increase the processing speed, a technique disclosed in JP-A-8-23539 is well known. In FIG. 38, the structure of the conventional moving picture coding apparatus is shown. In FIG. 38, a moving picture coding apparatus 5001 is structured by a variable length decoding means 5002 connected to an input means 5006, a re-quantizing means 5003, a variable coding means 5004, a buffer memory means 5005, and a buffer occupation amount detecting means 5006, and is connected to an output means 5008.

[0007] Next, an operation of the moving picture coding apparatus will be described. In FIG. 38, the input means 5007 inputs the coded moving picture data into the variable length decoding means 5002 for each one frame, and inputs the ~~objective~~desired bit rate into the re-quantization means 5003. Then, the variable length decoding means 5002 conducts variable length decoding on the input data, and the quantized DCT (Discrete Cosine Transform) coefficient is found, and outputted to the re-quantization means 5003. Then, the re-quantization means 5003 re-quantizes the quantized DCT coefficient, and outputs it to the variable length coding means 5004. In this connection, the re-quantization means 5003 compares the bit rate inputted from the input means 5007 to the buffer ~~occupation~~fullness amount inputted from the buffer occupation amount detecting means 5006, and the quantization value is set so as to satisfy a predetermined bit rate, and the re-quantization is conducted. Herein, the quantization value means a value to divide the DCT coefficient is divided in the quantization. Further, the variable length coding means 5004 conducts variable length coding on the re-quantized DCT coefficient, and supplies the moving picture data which is variable length coded, to the buffer memory means 5005. The buffer memory means 5005 outputs the inputted moving picture data from the variable length coding means 5004 to the output means 5008, and outputs the data amount of the moving picture data to the buffer occupation amount detecting means 5006. After the buffer occupation amount detecting means 5006

adds the data amount and detects the buffer occupation amount, the total amount of the data is outputted to the re-quantization means 5003.

[0008] As described above, when, by using the moving picture coding apparatus 5001, the bit rate is controlled from the compressioncompressed and coded moving picture data and the new moving picture data is newly produced, the moving picture data is produced through the process in which the input moving picture data is once variable length decoded, re-quantized, and variable length coded. That is, because the moving picture data is decoded and coded again [[to]]until the inverse quantization processing, the calculation load is large and it can be said that it is difficult to quickly conduct the rate control. Further, the moving picture data is structured by a plurality of frames, and because, when the moving picture data is compressioncompressed and coded, in order to increase the efficiency, generally, the correlation with the preceding frame by one frame in time is used, and theinterframe predictive coding, which is the process of using the correlation between the given frame and the immediately preceding frame, is generally between frames is used. Then, when the moving picture data includes the frame on which [[the]]interframe predictive coding between frames is conducted, [[the]]a problem exists when the re-quantization is conducted by using the moving picture coding apparatus.

[0009] WhenIn the interframe predictive coding between frames is used, the frame (Pi) on which [[the]] re-quantization is conducted in the moving picture coding apparatus 5001 is conducted, is used for using for the predictive coding

between frames in the subsequent frame (Pi+1) after one frame in time, and is the frame which is necessary for addition when the (Pi+1) is decoded when it is timewise at (Pi+1), which is the frame immediately following Pi. The frame Pi is necessary for decoding the (Pi+1) frame.

[0010] Then, when the re-quantization is conducted in the moving picture coding apparatus 5001, because the re-quantization means changes the quantization value of the input data, the frame (Pi) before theprior to re-quatization is conducted,differs from the frame (Pi') after the re-quantization is conducted. Accordingly, when the Pi' which is changed by the re-quantization, is added to the (Pi+1) on which the inverse quantization is conducted, and the (Pi+1) is decoded, the decoded image is deteriorated because the difference exists between the Pi to be originally added and Pi', the decoded image is deteriorated. Hereinafter, the difference between the Pi and Pi' is called as the motion compensation error. That is, to thefor moving picture data foron which theinter-frame predictive coding between frames is usedhas been conducted, when the moving picture data is produced by using the moving picture coding apparatus 5001, the image quality deterioration is caused due to the motion compensation error. Further, in order to prevent the image quality deterioration, it is necessary that the frame next to the frame on which the re-quantization is conducted, is re-corded including the motion compensation, and there is a problem that the processing time is further increased.

[0011] In the conventional moving picture coding apparatus, when the bit rate of the moving picture data which is previously coded, is changed, and the new moving picture data is newly produced, it is necessary to code again after the moving picture data is decoded once and re-quantized again[[,]]. Accordingly, ~~and~~ it is difficult to quickly produce the moving picture data.

[0012] When the conventional moving picture coding apparatus is used and the rate is controlled by ~~conducting~~performing the re-quantization, it is difficult to conduct the rate control without causing the image quality deterioration in the next frame on which the re-quantization is conducted[[,]]. This is ~~because the image quality deterioration~~ due to ~~the~~ motion compensation error~~ is caused, it is difficult to conduct the rate control without causing the image quality deterioration~~.

SUMMARY OF THE INVENTION

[0013] An object of the present invention is to solve the above mentioned two problems. That is, the object is that: when the bit rate of the coded moving picture data is changed, and the moving picture data is newly produced, the moving picture data production is quickly realized without decoding the moving picture data, and without causing the image quality deterioration due to the motion compensation error.

[0014] In order to solve the above problems, in a moving picture coding apparatus in which the previously ~~compression~~compressed and coded moving

picture data is an input, and the new moving picture data whose bit rate is different[[,]] is produced and outputted, the present invention is structured as follows.

[0015] ~~Firstly, the moving picture data producing apparatus to produce the moving picture data which is an input of the moving picture data coding apparatus, is provided with a producing means for a rate correction data in which the bit amount is different to an area in which the bit generation amount in the P frame (predictive coding image between frames) is large, and which can conduct the rate change.~~Firstly, a moving picture data producing apparatus, which creates moving picture data as an input for a moving picture coding apparatus, comprises a means to create a rate correction data with a different bit amount and a variable bit rate for the areas where the bit amount of a P-frame (interframe predictive coding picture) is large.

[0016] According to the above description, when [[the]]new moving picture data is ~~newly~~ produced from the previously coded moving picture data, by adjusting to the objective bit rate, and by selecting and replacing the rate correction data whose bit amount is different in the input moving picture data, the moving picture data production can be quickly conducted by changing the bit rate without decoding the moving picture data. Further, by producing the rate correction data in an area in which the bit amount is large, the bit rate change can be effectively conducted.

[0017] ~~Secondly, the moving picture data producing apparatus which produces the moving picture data which is an input of the moving picture coding apparatus is provided with a means by which the rate correction data in which the bit amount is different and the rate change can be conducted, is produced, to an area which is previously determined, and whose probability to be referred to from the next frame when the motion estimation is conducted, is low, in the P frame (predictive coding image between frames).~~<u>Secondly, the moving picture data producing apparatus comprises a means to create rate correction data with a different bit amount and a variable bit rate for the predetermined areas, which have a low likelihood of reference (low probability of being referred to) from the next frame for motion prediction within the P-frame.</u>

[0018] According to this, ~~when the~~<u>new</u> moving picture data ~~is newly~~<u>can be</u> produced from [[the]] previously coded moving <u>picture data</u>[[,]]<u>.</u> <u>This can be accomplished</u> by selecting and replacing the rate correction data ~~whose bit amount in the input moving picture data is different, by adjusting to the objective bit rate,~~<u>according to an objective bit rate.</u> [[the]]<u>The</u> bit rate is changed and the moving picture data can be quickly produced without decoding the moving picture data. Further, by producing the rate correction data [[in]]<u>for</u> an area ~~whose probability to be referred to~~<u>having a low likelihood of reference</u> from the next frame <u>(low probability of being referred to), a reduction of,</u> ~~is low, the lowering of~~ the predictive coding efficiency due to the influence of the search range limitation of the motion estimation can be reduced.

[0019] ~~Thirdly, the moving picture data producing apparatus to produce the moving picture data which is an input of the moving picture coding apparatus, is provided with a means f or producing the rate correction data whose bit amount is different, in the P frame, and provided with the motion compensation means for conducting the motion compensation without referring to from the area having the rate correction data, when the movement of the next frame is forecast.~~Thirdly, the moving picture data producing apparatus comprises a means to create a rate correction data in the P-frames having a different bit amount from the original bit amount, and a motion compensation means for conducting motion compensation without referring to the areas that include the rate correction data in the motion prediction for the next frame.

[0020] Accordin<u>gly</u>~~ to this~~, when the <u>new</u> moving picture data is ~~newly~~ produced from the previously coded moving picture data, even when the moving picture data is produced by selecting the rate correction data whose bit amount is different, in the input moving picture data, because the area is not subject to the motion estimation, the generation of the motion compensation error due to the replacement of the data can be prevented.

[0021] ~~Fourthly, the moving picture data producing apparatus to produce the moving picture data which is the input data of the moving picture coding apparatus, is provided with a means for producing the rate correction data whose bit amount is different, and which can change the bit rate, to an area in which the referred degree from the next frame when the movement is forecast, is low, in~~

the P frame.Fourthly, the moving picture data producing apparatus is provided with a means for producing the rate correction data whose bit amount is different, for an area having a low likelihood of reference from the next frame during motion prediction within the P-frame. In addition, the moving picture data producing apparatus can change the bit rate for such an area.

[0022] Accordingly, to the above description, when the moving picture data producing apparatus produces the moving picture data, the moving picture data can be produced without loweringreducing the coding efficiency of the interframe predictive coding between frames.

[0023] Fifthly, the moving picture data producing apparatus to produce the moving picture data which is the input data of the moving picture coding apparatus is provided with a means for producing the rate correction data, by removing the high frequency component of the original image, and by conducting the predictive coding between frames, to each P frame of the moving picture data.Fifthly, the moving picture data producing apparatus is provided with a means for producing the rate correction data, by removing the high frequency component of the original image, and by conducting the predictive coding between frames, for each P-frame of the moving picture data.

[0024] According to the above description, when the moving picture data is newly produced without decoding the previously coded moving picture data, corresponding to the objective bit rate, by selecting each area of the rate correction data coded by removing the high frequency component, the fine bit

~~rate control can be quickly conducted.~~According to the above description, when new moving picture data is produced without decoding the previously coded moving picture data, fine bit rate control can be quickly conducted according to the desired bit rate by selecting each area of the rate correction data coded by removing the high frequency component.

[0025] Sixthly, the moving picture data producing apparatus ~~to produce the moving picture data which is the input data of the moving picture coding apparatus~~ is provided with a means ~~for producing~~to create the area information, which identify deletable parts in the back part of ~~showing an area of the rear portion at which the bit can be deleted, in~~ each area, as the rate correction data.

[0026] According to the above description, in the moving picture coding apparatus which produces the new moving picture data from the coded moving picture data, ~~by adjusting to the objective bit rate, when each area of the input moving picture data is selected, and the rear portion bit is deleted, the bit rate control can be quickly conducted~~bit rate control can be quickly conducted according to the desired bit rate, when each area of the input moving picture data is selected, and the rear portion bit is deleted.

[0027] Seventhly, the moving picture data producing apparatus ~~to produce the moving picture data which is the input data of the moving picture coding apparatus~~ is provided with a means for ~~producing the~~creating an I-frame ~~whose bit amount is different, as the rate correction data, to~~for each P-frame as a rate

correction data, wherein each I-frame has a different bit amount corresponding to the respective P-frame.

[0028] ~~According to this, in the moving picture coding apparatus which produces the new moving picture data from the previously coded moving picture data, by adjusting to the objective bit rate, and by replacing P frame of the input moving picture data with the I frame whose bit amount is different which is the rate correction data, the bit rate control can be quickly conducted without decoding the input moving picture data.~~Accordingly, in the moving picture coding apparatus, bit rate control can be quickly conducted according to the desired bit rate without decoding the input moving picture data, by replacing the P-frame of the input moving picture data with the I-frame whose bit amount is different and which is the rate correction data.

[0029] ~~Eighthly, in the case where the moving picture data producing apparatus to produce the moving picture data which is the input of the moving picture coding apparatus is provided with a means for determining the quarry out area in each frame, and for producing the rate correction data by which the rate correction is possible, for at least an area more than one in each quarry out area in the frames, and a motion compensation means for inhibiting the motion estimation outside the area having the rate correction data in the preceding frame at the time of motion compensation and the quarry out area, when one portion in the frame is quarried out from the previously coded moving picture data and the moving picture data is newly produced, corresponding to the objective bit~~

~~rate, by selecting the data whose bit amount is different, the bit rate is controlled and the moving picture data can be quickly produced without decoding the moving picture data. Further, because the motion estimation to the outside of the quarried out area is not conducted, even by using only the quarried out area of a portion of the frame, the decoding can be conducted without generating the motion compensation error.~~Eighthly, the moving picture data producing apparatus produces moving picture data. Said moving picture data is an input of the moving picture coding apparatus. The moving picture data producing apparatus is provided with a means for: determining the select and remove area in each frame; and for producing the rate correction data by which the rate correction is possible for at least more than one area in each selected and removed area in the frames. The moving picture data producing apparatus is further provided with a motion compensation means for inhibiting the motion estimation outside of the areas having the rate correction data in the preceding frame at the time of motion compensation and the select and remove areas. When one portion in the frame is selected and removed from the previously coded moving picture data and the new moving picture data is produced according to the desired bit rate, by selecting the data whose bit amount is different, the bit rate is controlled and the moving picture data can be quickly produced without decoding the moving picture data. Further, because motion estimation is not conducted outside of the selected and removed area, even by

using only the selected and removed area of a portion of the frame, the decoding

can be conducted without generating the motion compensation error.

BRIEF DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0030] FIG. 1 is a block diagram showing the structure of a moving picture

data producing apparatus in the first embodiment of the present invention;

[0031] FIG. 2 is a block diagram showing the structure of a moving picture

coding apparatus in the first embodiment of the present invention;

[0032] FIG. 3 is a block diagram showing the structure of the moving picture

data producing apparatus in the second embodiment of the present invention;

[0033] FIG. 4 is a block diagram showing the structure of the moving picture

data producing apparatus in the third embodiment of the present invention;

[0034] FIG. 5 is a block diagram showing the structure of the moving picture

data producing apparatus in the fourth embodiment of the present invention;

[0035] FIG. 6 is a block diagram showing the structure of the moving picture

data producing apparatus in the fifth embodiment of the present invention;

[0036] FIG. 7 is a block diagram showing the structure of the moving picture

coding apparatus in the fifth embodiment of the present invention;

[0037] FIG. 8 is a block diagram showing the structure of the moving picture

data producing apparatus in the sixth embodiment of the present invention;

[0038] FIG. 9 is a block diagram showing the structure of the moving picture

coding apparatus in the sixth embodiment of the present invention;

[0039] FIG. 10 is a view showing an example of an area dividing the inside of the frame in the first embodiment of the present invention;

[0040] FIG. 11 is a view showing a compression frame buffer structure in the first embodiment of the present invention;

[0041] FIG. 12 is a view showing the rate correction area data in the first embodiment of the present invention;

[0042] FIG. 13 is a view showing the compression frame data in the first embodiment of the present invention;

[0043] FIG. 14 is a view showing the moving picture data structure in the first embodiment of the present invention;

[0044] FIG. 15 is a view showing the data structure of the rate correction data in the first embodiment of the present invention;

[0045] FIG. 16 is a view showing the content of the rate correction data in the first embodiment of the present invention;

[0046] FIG. 17 is a view showing the rate correction data header structure in the first embodiment of the present invention;

[0047] FIG. 18 is a view showing the referred area data in the third embodiment of the present invention;

[0048] FIG. 19 is a view showing the compression frame data in the fourth embodiment of the present invention;

[0049] FIG. 20 is a view showing the rate correction data header structure in the fourth embodiment of the present invention;

[0050] FIG. 21 is a view showing the structure of the moving picture coding apparatus in the fourth embodiment of the present invention;

[0051] FIG. 22 is a view showing a flow of a rate control method in the fourth embodiment of the present invention;

[0052] FIG. 23 is a view showing the structure of a ~~Video Packet~~video packet in the fifth embodiment of the present invention;

[0053] FIG. 24 is a view showing the ~~Video Packet~~video packet termination data structure in the fifth embodiment of the present invention;

[0054] FIG. 25 is a view showing the rate correction data structure and the rate correction data header structure in the fifth embodiment of the present invention;

[0055] FIG. 26 is a view showing the data content of the rate correction data in the fifth embodiment of the present invention;

[0056] FIG. 27 is a view showing the rate correction data structure and the rate correction data header structure in the sixth embodiment of the present invention;

[0057] FIG. 28 is a view showing the data content of the rate correction data in the sixth embodiment of the present invention;

[0058] FIG. 29 is a view showing the structure of the moving picture data producing apparatus in the seventh embodiment of the present invention;

[0059] FIG. 30 is a view showing an example of a quarry out area in the 1 frame in the seventh embodiment of the present invention;

[0060] FIG. 31 is a view showing the rate correction area data structure in the seventh embodiment of the present invention;

[0061] FIG. 32 is a view showing the compression frame data structure in the seventh embodiment of the present invention;

[0062] FIG. 33 is a view showing the rate correction data structure in the seventh embodiment of the present invention;

[0063] FIG. 34 is a view the rate correction data header structure in the seventh embodiment of the present invention;

[0064] FIG. 35 is a view showing the structure of the moving picture coding apparatus in the seventh embodiment of the present invention;

[0065] FIG. 36 is a view showing the Video Packet structure data in the fifth embodiment of the present invention;

[0066] FIG. 37 is a view showing the structure of I-frame coding means in the sixth embodiment of the present invention; and

[0067] FIG. 38 is a block diagram showing the structure of the moving picture coding apparatus which is the conventional technology.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0068] By using FIG. 1 to FIG. 37, embodiments of the present invention will be described below. In this connection, the present invention is not limited to these embodiments, but in the range not departing from the spirit of the invention, the present invention can be conducted in various modes.

[0069] Embodiment 1

[0070] In the first embodiment, a moving picture coding apparatus ~~by which~~ ~~the~~for performing data rate control ~~is conducted~~ without decoding ~~by using the~~ previously ~~compression~~compressed and coded moving picture data, and the new moving picture data ~~is newly~~ produced, and its method will be described below.

[0071] Initially, the moving picture data producing apparatus which previously produces the moving picture data which is an input of the moving picture coding apparatus, will be described below.

[0072] ~~In~~ FIG. 1[[,]]shows the structure of the moving picture data producing apparatus to ~~previously~~ produce the moving picture data having the data structure to quickly conduct the rate control~~, is shown~~.

[0073] In FIG. 1, a moving picture data producing apparatus 101 is provided with[[:]] a frame input means 117 connected to an input means 116; motion compensation means 102; DCT conversion means 103; quantizing means 104; variable length coding means 105; inverse quantizing means 106 to conduct the decoding; inverse DCT conversion means 107; and a frame memory 108 to store the decoded frame~~, and is provided with:~~ a maximum bit amount area detecting means 110 which is connected to the variable length coding means 105 and successively detects an area having the maximum bit amount; reference inhibition area memory means 109; compression frame buffer 112 connected to the DCT conversion means 103; quantization means 111 which is connected to the compression frame buffer 112 and conducts the quantization; ~~and~~ variable

length coding means 113;, and is provided with: a compression frame data combination means 114 which is connectedcombines the moving picture data is connected to the variable length coding means 105, reference inhibition area memory means 109 and variable length coding means 113., and combines with the The moving picture data producing apparatus 101, and has the structure to be is connected to an output means 115.

[0074] The operation of the thus structured moving picture data producing apparatus will be described below.

[0075] Initially, the input means 116 inputs the non-compression image into the frame input means 117. When the frame input means 117 receives the frame coding end signal inputted from the compression frame data combination means 114, the non-compression one frame data inputsnon-compressed data for a frame is inputted into the motion compensation means 102. However, when the first frame data is inputted, it is independent fromnot related to the frame coding end signal, and simultaneously when the data is inputted from the input means 116, the non-compressionnon-compressed frame data is inputted into the motion compensation means 102.

[0076] Then, when the motion compensation means 102 conducts the predictive coding between frames on the non-compression frame data inputted from the frame input means 117, after the area whose correlation is high in the preceding frame by one frame inputted from the frame memory 108 is detected, it conducts the subtraction, and outputs the subtracted frame data to the DCT

~~conversion means 103. In this case, the motion compensation means 102 does not conduct the motion detection from the reference inhibition area of the preceding frame by one frame inputted from the reference inhibition area memory means 109. Further, it does not conduct the motion compensation on the data on which the coding in the frame is conducted, and the input data is outputted to the DCT conversion means as it is.~~Then, the motion compensation means 102 conducts the interframe predictive coding on the data it has received. It does this by detecting the area whose correlation is high in the immediately preceding frame. The immediately preceding frame is inputted from the frame memory 108. It then performs a subtraction, and outputs the subtracted frame data to the DCT conversion means 103. In this case, the motion compensation means 102 does not perform a motion detection from the reference inhibition area of the preceding frame, which is inputted from the reference inhibition area memory means 109. Further, it does not perform a motion compensation on the data on which the coding in the frame is conducted, and the input data is outputted to the DCT conversion means 103 unchanged.

[0077] The DCT conversion means 103 conducts the DCT conversion on the frame data ~~which is inputted~~provided by the motion compensation means 102~~,~~ ~~and outputs the~~ The DCT conversion means 103 then outputs the DCT coefficient to the quantization means 104 and the compression frame buffer 112.

[0078] ~~In FIG. 10, an example of the dividing method of an area in the frame is shown. Herein, the area shown in FIG. 10 is structured by an arbitrary number~~

~~of macro-blocks (for example, 16.times.16 pixels), and any shape maybe allowable, and is not limited to the shape shown in FIG. 10. Further, the structure of the compression frame buffer is shown in FIG. 11. The compression frame buffer respectively continuously accommodates the quantization amount and the DCT coefficient, corresponding to each area in FIG. 10.~~FIG. 10 shows an example of a method of dividing an area in a frame. The area shown in FIG. 10 is structured by an arbitrary number of macro-blocks (for example, 16 x 16 pixels). However, any shape may be allowable, and the area is not limited to the shape shown in FIG. 10. Further, the structure of the compression frame buffer is shown in FIG. 11. The compression frame buffer continuously accommodates the quantization amount and the DCT coefficient corresponding to each area in FIG. 10.

[0079] The quantization means 104 quantizes the DCT coefficient obtained by the DCT conversion means 103 for each area shown in FIG. 10[[, and the]]. The quantized DCT coefficient is then outputted to the inverse quantization means 106 and the variable length coding means 105, ~~and~~while the quantization value used for the quantization is outputted to the compression frame buffer 112. ~~The~~As shown in Fig. 11, the compression frame buffer 112 makes the DCT coefficient ~~for one frame inputted by the DCT conversion means 103~~and the quantization value for each area shown in FIG. 10~~, and the quantization value inputted by the quantization means 104 respectively~~ correspond to each other ~~as shown in FIG. 11~~, and then stores them.

[0080] The variable length coding means 105 conducts the variable length coding on the quantized DCT coefficient, and outputs it to the maximum bit amount area detecting means 110 and the compression frame data combination means 114. Herein, the data which is coded by the variable length coding means 105 is called the normal frame data.

[0081] Further, the inverse quantization means 106 conducts theperforms an inverse quantization on the quantized DCT coefficient quantized by the quantization means 104, and outputs itthe result to the inverse DCT conversion means 107. The inverse DCT conversion means 107 conducts theperforms an inverse DCT conversion on the DCT coefficient obtained inprovided by the inverse quantization means 106, and outputs it to the motion compensation means 102. The motion compensation means 102 decodes the frame by using the inverse DCT converted coefficient and the decoding frame, which is the immediately preceding frame by one frame inputted by the frame memory, and renews the decoding frame of the frame memory. In addition, the motion compensation means 102 updates the decoding frame stored in the frame memory. However, for the I-frame, the inverse DCT converted frame is stored in the frame memory as it isunchanged.

[0082] As described above, in the variable length coding means 105, when the coding of one frame is completed, the maximum bit amount detecting means 110 detects a predetermined number of areas in order of area having the larger bit amount from the area including the maximum bit amount, in the frame coded

~~by the variable-length coding means 105, and outputs the rate correction area data showing the detected areas to the reference inhibition are a memory means 109 and the compression-frame buffer 112. In FIG. 12, an example of the rate correction area data is shown. In FIG. 12, a black area shows the selected areas by the frame-maximum-bit area detecting means, and this area is defined as the reference-inhibition area.~~ As described above, when the coding for one frame is completed, the maximum bit amount area detecting means 110 detects a predetermined number of areas from the encoded frames(encoded by the variable length coding means 105) in the order of bit amount starting from the maximum, and then outputs the rate correction area data, which indicates the detected area, to the reference inhibition area memory means 109 and the compressed frame buffer 112. FIG. 12 shows an example of the rate correction area data. In FIG. 12, shaded areas indicate the areas selected by the frame maximum bit area detecting means, and this area is defined as the reference inhibition area.

[0083] The reference inhibition area memory means 109 outputs the <u>rate</u> correction area data ~~showing the detected area by the maximum-bit-amount area detecting means 110~~ to the motion compensation means 102 and the ~~moving picture~~<u>compression frame</u> data combination means 114. Then, the compression frame buffer 112 cuts out the DCT coefficient and the quantization value [[of]]<u>for</u> the ~~area~~corresponding<u> area,</u> from <u>within</u> the ~~inside of the~~compression frame buffer, [[to]]<u>for</u> the reference inhibition area of the correction area data<u>, which is</u>

inputted by the maximum bit amount area detecting means 110, and outputs them to the quantization means 111. The quantization means 111 ~~conducts theperforms~~ a quantization ~~by using a plurality of quantization value s before and after the quantization value s inputted from the compression frame buffer 112, on the DCT coefficient inputted from the compression frame buffer 112, and outputs it to the variable length coding means 113.~~on the DCT coefficient inputted from the compression frame buffer 112 and outputs it to the variable length coding means 113. It does this by using a plurality of quantization values before and after the quantization values inputted from the compression frame buffer 112. That is, it uses several quantization values around the value inputted from the compression frame buffer.

[0084] In the quantization means 111, when the quantization is conducted by using the different quantization value, the data whose bit amount is different can be produced.

[0085] For example, when the quantization is conducted by the quantization value Q=2, on the input stream in which an image plane size is CIF (352 x 288) and the frame rate is 30 fps, and the MPEG 4 stream is ~~made~~created, the bit rate is about 1.6 Mbps~~, and like as~~. Similarly, at Q=6, the bit rate is about 384 kbps, at Q=16, about 128 kbps, and at Q=30, about 56 kbps~~, the data whose bit rate is different,~~. Different bit rates, can be produced corresponding to ~~the~~different quantization value~~s~~ Q.

[0086] The variable length coding means 113 conducts variable length coding on the DCT coefficient quantized by the quantization means 111, and produces the correction data, ~~and produces~~ the rate correction data having the number of areas, the number of correction data of each area, the area number and the data size of respective correction data as the header information, and outputs it to the compression frame data combination means 114. Herein, the data produced by the variable length coding means 113 is defined as the rate correction data. In FIG. 15, the structure of the rate correction data is shown~~, and the~~. The content of the rate correction data is shown in FIG. 16. ~~Further, the~~The structure of the rate correction data header is shown in FIG. 17. In FIG. 17, the rate correction data header 1502 has a structure in which the number in each area of the correction data whose bit amount is different, which is produced by changing the number of areas and the quantization value, and the area number and the bit amount of respective correction data are stored as the fixed length data. Herein, the ~~order of~~ areas ~~is defined as the order in which the bit amount is larger~~are stored in descending order according to the bit amount. Then, in FIG. 15, the rate correction data ~~has the structure in which the correction data is stored succeeding to the rate correction data header 1502 in order of the area in which the bit amount of the correction data is larger~~are stored in descending order according to the bit amount, following the rate correction data header 1502. The structure of the compression frame data is shown in FIG. 13~~. In FIG. 13,~~ where the compression frame data ~~has~~is shown with a structure in which the rate

correction area data and the rate correction data are successively stored after the normal frame data.

[0087] The compression frame data combination means 114 stores the normal frame data inputted by the variable length coding means 105, the correction area data inputted by the reference inhibition area memory means 109, and the rate correction data inputted by the variable length coding means 113 in order, as shown in FIG. 13, and outputs them. The compression frame data combination means 114 outputs this information as the compression frame data 1301 to the output means 115[[, and]]. It further outputs the frame coding end signal, showing that the coding of one frame is completed, to the frame input means 117. The structure of the moving picture data is shown in FIG. 14. In FIG. 14, where the moving picture data 1401 hasis shown with a structure in which the compression frame data is successively stored.

[0088] Thus coded moving picture data 1401 has a structure in which, for each frame, the normal frame data, the rate correction area data showing the area in which the rate correction data exists, and the rate correction data whose bit amount is different, are arranged in order. Then, the area having the rate correction data, that is, the reference inhibition area, inhibits the reference from the next frame at the time of motion estimation, and because it is in the condition that the motion estimation is not received from the next frame, even when the data of this area is replaced with the rate correction data and the bit rate change

is conducted, the motion compensation error is not generated when the next frame is decoded.

[0089] Next, the structure of the moving picture coding apparatus by which the moving picture data coded by the moving picture coding apparatus shown in FIG. 1 is used as the input data, and the rate control is conducted without decoding the input data, and the rate changed moving picture data is newly produced, is shown in FIG. 2.The structure of the moving picture coding apparatus 201 is shown in Fig. 2. The moving picture coding apparatus 201 codes the moving picture data, which it receives from the moving picture data producing apparatus 101. Rate control is conducted without decoding the input data and new rate changed moving picture data is produced.

[0090] In FIG. 2, the moving picture coding apparatus 201 has a data separation means 207 connected to an input means 202, bit amount calculation means 203, rate correction data selection means 204, bit rate control means 205 and moving picture combination means 208, and has a structure in which it is connected to an output means 206.

[0091] The operation of thus structuredthe moving picture coding apparatus 201 will be described below. In FIG. 2, the input means 202 inputs the compressioncompressed and coded moving picture data 1301 and the objectivedesired bit rate which is determined by the user, to the data separation means 207. When the data is inputted by the input means 202, the data separation means 207 inputs the objectivedesired bit rate for a frame by each

~~one frame~~ to the bit rate control means 205~~, and further, takes out the data in~~ ~~order from the leading data of the inputted moving picture data, and inputs the~~ ~~normal frame data for each one frame to the bit amount calculation means 203,~~ ~~and inputs the rate correction area data and the rate correction data for each one~~ ~~frame to the rate correction data selection means 204~~. The data separation means 207 also takes out the data in order from the leading data (first to last), and inputs the normal frame data for a frame to the bit amount calculation means 203. In addition, that data separation means 207 inputs the rate correction area data and the rate correction data for a frame to the rate correction data selection means 204. When~~Herein, when~~ the input means 202 inputs the frames other than the first ~~one~~ frame of the moving picture data, after the frame coding end signal is received from the rate correction data selection means 204, it conducts the respective data input.

[0092] The bit amount calculation means 203 calculates the bit amount of the inputted normal frame data[[, and]]. It outputs the bit amount to the bit rate control means 205, and ~~outputs~~ the normal frame data to the rate correction data selection means 204.

[0093] ~~The bit rate control means 205 compares the objective bit rate inputted~~ ~~from the inputted means 202 to the current bit amount inputted from the bit~~ ~~amount detecting means 203, and the insufficient bit amount necessary for~~ ~~satisfying the objective bit rate, or sufficient bit amount is obtained, and is~~ ~~outputted to the rate correction data selection means 204.~~ The bit rate control

means 205 compares the desired bit rate to the current bit amount inputted from the bit amount calculation means 203. The bit rate control means 205 obtains the excessive or insufficient bit amount necessary for achieving the desired bit rate. The excessive or insufficient bit amount necessary for achieving the desired bit rate is outputted to the rate correction data selection means 204.

[0094] ~~The rate correction data selection means receives the bit amount which is a bit rate error, inputted by the bit rate control means 205, and in order to satisfy the objective bit rate, to the area shown by the rate correction area data inputted by the data separation means 207, it compares the bit amount of the area in the normal frame data to the bit amount of the plurality of correction data stored in the rate correction data header 1502, and when the data is replaced, the correction data by which the bit rate error becomes small, is selected in order of stored areas, and by replacing the data in the normal frame data with selected correction data, the bit amount is changed. Further, when the bit amount error is large, the correction data is selected from the next area, and by replacing the data, the bit amount is changed. By repeating the above processing, the moving picture data in which the bit amount error is made minimum, is outputted to the moving picture data combination means 208, and one frame coding end signal is outputted to the data separation means 207.~~ In order to satisfy the desired bit rate, the rate correction data selection means 204 receives the bit amount which is a bit rate error from the bit rate control means 205. For the area shown by the rate correction area data inputted by the data separation means 207, the rate

correction data selection means 204 compares the bit amount of the area in the normal frame data to the bit amount of the plurality of correction data stored in the rate correction data header 1502. When the data is replaced, the correction data for reducing the bit rate error is selected in order of stored areas. By replacing the data in the normal frame data with selected correction data, the bit amount is changed. Further, when the bit amount error is large, the correction data is selected from the next area, and by replacing the data, the bit amount is changed. By repeating the procedure above, the moving picture data in which the bit amount error is reduced, is outputted to the moving picture data combination means 208, and one frame coding end signal is outputted to the data separation means 207.

[0095] The moving picture data combination means 208 connects the frame data inputted for each frame from the rate correction data selection means 204 in order, and produces the moving picture data and outputswhich is outputted to the output means 206.

[0096] Herein, when the area is selected by the rate correction data selection means 204 and the data is replaced corresponding to the bit amount, there is a problem in that the motion compensation error is caused by the replacement of the data which is referred to as the motion compensation after I-frames in the conventional method, and theresulting in image quality deterioration is caused, however. However, in the present invention, motion compensation error is not created, because the reference to the area having the rate correction data is

inhibited by the reference inhibition area memory means ~~109 in the moving picture data producing apparatus in FIG. 1~~, even when the correction data is selected and replaced, ~~the motion compensation error is not caused~~. Accordingly, the rate control can be quickly conducted by selecting the correction data without decoding the moving picture data and without causing the image quality deterioration due to the motion compensation error.

[0097] Further, in the present embodiment, the number of areas detected by the maximum bit area detecting means 110 is determined by the user corresponding to[[, to]] what [[%]]percent the bit rate of the input data can be changed, and the larger the number of areas[[is]], the larger the range of the bit rate ~~change is~~changes. However, when the number of areas is increased, ~~because the reference area used for the motion estimation becomes narrow,~~ the coding efficiency ~~is lowered~~decreases, because the reference area used for the motion estimation becomes lower. In order to solve the problem, the maximum bit area detecting means 110 detects the area, from the area having the maximum bits, in the order ~~in which~~of the bit amount ~~is larger~~from the largest. It is because the ~~compression~~compressed and coded data does not always have a uniform bit amount in the frame[[,]] and there are cases where the area having the larger bit amount exists locally, ~~and when~~if the correction data is provided ~~to such~~in the area ~~in which the~~having a large bit amount~~is large~~, the bit rate change becomes ~~easy~~simple, and the reference inhibition area can be reduced.

[0098] Further, the number of rate correction data of each area selected by the maximum bit area detecting means 110 and the value of respective quantization value also contribute to the width of the bit rate change. For example, when the quantization of the normal frame data is conducted at Q=6, ~~the~~its bit rate is about 384 kbps, and ~~as the area having the rate correction data, a plurality of areas having the data amount of about 3/4 of the whole in total are selected from the areas whose bit amount is large~~the several areas, which have correction data with the data amount about 3/4 of the total, are selected in the order of bit amount from the largest. When the deviation of the bit is considered, ~~an area~~size of the areas is ~~lower~~less than 3/4. For these areas, by using the quantization values Q=2, Q=30, two kinds of rate correction data of about 1.6 Mbps, and about 56 kbps are produced. Whole data size including the rate correction data is about 1.6 Mbps. ~~When~~The bit rate of the moving picture data including the rate correction data is ~~combined with the rate correction data, the bit rate change can be arbitrarily conducted in the range of about~~variable within about 1.5 Mbps to ~~about~~64 kbps~~, and the moving picture data matched with bit rates of various transmission paths can be produced~~ by changing the combination of the rate correction data, and the moving picture data can be matched to the bit rates of various transmission paths.

[0099] Further, the calculation cost relating to the rate change is low, and a plurality of streams ~~in which bit rates are different,~~having different cit rates can be quickly produced. Further, when the streams~~ whose bit rate is different is~~are

prepared ~~from the initial time~~initially, the bit rate~~s~~ [[is]]are fixed and [[its]]the data size becomes large. ~~Comparing to that case, in the present embodiment, it is enough when the data size is slightly larger than the maximum bit rate which is presumed~~Compared with such a condition, a slightly larger bit rate than the presumed maximum bit rate is a sufficient data size for the present embodiment.

[0100] As described above, in the present embodiment, the motion compensation means, which does not conduct the motion compensation from the reference inhibition area, and the moving picture data producing apparatus, which produces the moving picture data ~~having together~~along with the rate correction data, and the area selection means, which selects the rate correction data corresponding to the bit rate, are provided, ~~thereby,~~. Accordingly the apparatus can quickly ~~conduct the~~perform rate control without decoding the moving picture data[[,]] and without causing [[the]] image quality deterioration due to [[the]] motion compensation error, ~~and~~. In addition, the apparatus can quickly produce a plurality of streams in which the bit rate is different, ~~thereby, its practical effect is large~~.

[0101] Embodiment 2

[0102] ~~In the~~The second embodiment[[,]] will be discussed below. It is an apparatus ~~in which the~~for performing rate control ~~is conducted from the previously~~without decoding coded moving picture data ~~without being decoded, and the moving picture data is newly produced~~, and ~~which is~~further characterized in that, [[as]]for the area selection method to produce the rate correction data, the

known area to which is hardly referred to the likelihood of reference at the time of motion estimation is low, is used, will be described below.

[0103] In the present embodiment, the moving picture coding apparatus 201 by which the rate change is conducted from the previously coded moving picture data, and the moving picture data is newly producedit produces, [[is]]are the same as in Embodiment 1.

[0104] A moving picture data producing apparatus by which thefor producing moving picture data, which is an input [[of]]to the moving picture coding apparatus to quickly conduct the rate control, is previously produced, will be described below.

[0105] In FIG. 3, the structure of the moving picture data producing apparatus by which the moving picture data having the data structure to quickly conduct the rate control is produced301, is shown. The apparatus produces moving picture data structured for quick performance of rate control.

[0106] In FIG. 3, the moving picture data producing apparatus 301 is provided with: a frame input means 117 connected to an input means 116; motion compensation means 102; DCT conversion means 103; quantization means 104; variable length coding means 105; inverse quantization means 106 for conducting the decoding; inverse DCT conversion means 107; and frame memory 108 for storing the decoded frame, and the apparatus is connected to the variable length coding means 105, and is provided with: the rate correction area selection means 310 for selecting the area producing the rate correction

data; reference inhibition area memory means 109; compression frame buffer 112 to connect to the DCT conversion means 103; quantization means 111 to connect to the compression frame buffer and to conduct the quantization; and variable length coding means 113, and is connected to the; variable length coding means 105[[,]]; and reference inhibition area memory means 109, and variable length coding means 113, and is provided with a compression frame data combination means 114 to combine the moving picture data, and has a structure which is connected to an output means 115. The moving picture data producing apparatus 301 is further provided with a compression frame data combination means 114 to combine the moving picture data. The compression frame data combination means 114 is connected to both the variable length coding means 105, 113, the reference inhibition are memory means 109, and the output means 115.

[0107] Operations of thus structured moving picture coding apparatus will be described below.

[0108] In FIG. 3, operations other than the rate correction selection means 310 are entirely the same as in Embodiment 1. In FIG. 3, the variable length coding means 105 conducts the variable length coding on the quantized DCT coefficient inputted from the quantization means 104 in the same manner as in Embodiment 1, and outputs it to the rate correction area selection means 310 and the compression frame data combination means 114. Herein, the data coded by the variable length coding means 105 is called the normal frame data.

[0109] As described above, when the coding of the normal frame data is completed, the rate correction data area selection means 310 selects the area for the rate correction from the frame coded in the variable length coding means 105, and outputs the rate correction area data 1201 ~~showing~~indicating the selected area as shown in FIG. 12, to the reference inhibition area memory means 109 and the compression frame buffer 112. Herein, the area selected as the rate correction area is an area to which the ~~probability to be referred from~~likelihood of reference by the next frame at the time of the motion estimation, is low, for example, such as a rim portion of the frame, and is defined as the known area which is previously stored in the rate correction data area selection means 310.

[0110] ~~In the present embodiment, it is inhibited that the area for rate correction is referred to at the time of motion estimation, and by inhibiting the reference, because the search area at the time of motion estimation is small, there is a possibility that the predictive coding efficiency is lowered. Therefore, the area which is hardly referred to at the time of motion estimation, is defined in such a manner that it is selected as the rate correction area. Thereby, even when the search area at the time of motion estimation becomes small, because the area has the small probability to be originally referred to, the practical search area is not small, that is, the predictive coding efficiency can be prevented from lowering. Operations after the compression frame buffer 112 are the same as in Embodiment 1.~~In the present embodiment, reference to the rate correction area

at the time of motion estimation is inhibited. This may reduce predictive coding efficiency because the search area at the time of motion estimation is small. Therefore, the area that is less likely to be referred to (low probability of being referred to) at the time of motion estimation, is selected as the rate correction area. Accordingly, even when the search area at the time of motion estimation becomes small, because the area has a low likelihood to be originally referred to, the practical search area is not small. In other words, it is possible to prevent a reduction in the predictive coding efficiency. Operations after the compression frame buffer 112 are the same as in Embodiment 1.

[0111] Thus coded moving picture data has the following structure having, tofor each frame[[,]]: the compression coded normal frame data, rate correction area data showing the area in which the rate correction data exists, and rate correction data including a plurality of correction data whose bit amounts [[is]]are different[[, and]]. Furthermore, the area having the rate correction data is in the conditionsuch that it is not referred to at the time of motion estimation from the next frame.

[0112] As described above, when the coded moving picture data is an input, and by using the moving picture coding apparatus 201 shown in FIG. 2[[,]] in the same manner as in Embodiment 1, [[the]] rate correction data corresponding to the objectivedesired bit rate is selected[[,]] and it is replaced with thereplaces data in the normal frame data[[, by]]. By producing the new moving picture data,

[[the]] rate control ~~can be quickly conducted without decoding the data~~<u>without decoding can be quickly conducted</u>.

[0113] Further, the area to produce the rate correction data is defined as the known area, such as the rim portion of the frame which is ~~hardly~~<u>less likely to be</u> referred to at the time of motion estimation, and the size of the area can be determined by the user corresponding to the range of the change of the bit rate. Further, the number of the rate correction data and the quantization value in each area also contribute to the width of the bit rate change.

[0114] For example, when the quantization of the normal frame data (size: CIF, frame rate 30 fps) is conducted at $Q=24$, the bit rate becomes about 100 kbps. [[To]]<u>Contrary to</u> this, the area ~~of the size of total of~~<u>in which motion estimation is less likely to be conducted and whose size is in total</u> about 40% ~~at the ratio of the area~~of the frame <u>(are ratio)</u>, ~~in which the motion estimation is hardly conducted,~~is defined as the rate correction data area~~, and on respective~~<u>.</u> <u>On said rate correction data</u> area ~~data~~, the quantization is conducted at [[the]]two quantization values $Q=16$ and 31, and the rate correction data having the bit rate corresponding to about 128 kbps, and about 32 kbps are produced. With the moving picture data having these rate correction data, when the rate correction data is combined, the bit rate can be arbitrarily changed between about 128 kbps and about 64 kbps, and the moving picture data corresponding to the fluctuation of the band of the transmission path can be quickly produced. Further, the calculation cost according to the bit rate change is low, and a

plurality of moving picture data whose bit rate is different, can be quickly produced.

[0115] In the present embodiment, the range of the bit rate change is smaller as ~~compared to~~than that of Embodiment 1~~, but~~. However, in the present ~~invention is characterized in that~~embodiment, because the area which is set as the reference inhibition area~~, has the character which is hardly forecast, the lowering of the coding efficiency can be prevented~~is less likely to be predicted, reduction of the coding efficiency can be prevented. Further, the data size of the moving picture data is about 128 kbps, and almost equal to the maximum value of the bit rate change.

[0116] ~~As described above, in the present embodiment, when the moving picture data producing apparatus in which a plurality of rate correction data whose bit amount are different, are produced, to the area to which the probability to be referred at the time of motion estimation is low, and the control means which is matched with the objective bit rate, and selects the rate correction data, and conducts the rate control, are provided, because the predictive coding efficiency at the time of motion estimation is not lowered, and the rate control can be quickly conducted without causing the image quality deterioration due to the motion compensation error, a plurality of moving picture data whose bit rates are different, can be quickly produced, thereby, its practical effect is large.~~As described above, the present embodiment provides a motion picture data producing apparatus, which creates several rate correction data with a different

bit amount for the area less likely to be referred to at the time of motion estimation. This embodiment also provides a rate controlling means, which selects rate correction data and controls the rate corresponding to the desired bit rate. These elements make possible high-speed rate controlling without either the reduction of predictive coding efficiency at the time of motion estimation or image quality degradation caused by motion compensation error, and the high speed creation of several motion picture data with different bit rates.

[0117] Embodiment 3

[0118] In the third embodiment, described below, the moving picture data producing apparatus has in which the rate control is conducted from the previously coded moving picture data without being decoded, and the moving picture data is newly produced, wherein the apparatus has, to the moving picture data, by using the referred degree at the time of the motion estimation, a means for selecting the rate correction area to produce a plurality of data in which the bit amount is different, will be described below.

[0119] Further, in the present embodiment, the moving picture coding apparatus in which the rate control is conducted from the previously coded moving picture data, and the moving picture data is newly produced, is entirely the same as in Embodiment 1.

[0120] The structure of the moving picture data producing apparatus is shown in FIG. 4. In FIG. 4, a moving picture data producing apparatus 401 has: a frame input means 117 connected to an input means 116; motion compensation means

402; DCT conversion means 103; quantization means 104; variable length coding means [[105]]405; inverse quantization means [[105]]106 for decoding; inverse DCT conversion means 107; [[and]] frame memory 108 for storing the decoded frame[[, and]]; a referred area memory means 410 connected to a motion compensation means 402; and a rate correction area selection means 412[[, and]]; a compression frame buffer 112 connected to a DCT conversion means [[404]]103; quantization means 111; and variable length coding means 113, and a rate correction area selection means 412; compression frame combination means 414 connected to the variable length coding means 113 and variable length coding means 105, and has a structure in which these means are connected to the; and an output means 115.

[0121] Operations of thus structured moving picture producing apparatus will be described below. In the moving picture coding apparatus 401, the input means 116, frame input means 117, DCT conversion means 103, quantization means 104, variable length coding means 105, inverse quantization means 106, inverse DCT conversion means 107, and frame memory 108 produce the normal frame data in entirely the same manner as in Embodiment 1. In this connection, the variable length coding means 405 outputs the frame coding end signal to the frame input means 117 when the normal frame data producing is completedhas been produced. In this manner, when the normal frame data for one frame is produced, the frame input means 117 outputs the next non-compression frame to the motion compensation means 402.

[0122] ~~The motion compensation means 402 does not conduct the motion compensation on the I frame, and outputs to the DCT conversion means 103, and in the case of other than I frame, the motion compensation is conducted by using the preceding frame by I frame and the frame inputted by the frame input means 117. Further, in the preceding frame by 1 frame, the area information which is referred to at the time of motion estimation, is outputted to the referred area memory means 410.~~The motion compensation means 402, which outputs to the DCT conversion means 103, does not conduct the motion compensation on the I-frame. In the case of other than I-frames, the motion compensation is conducted by using the immediately preceding frame and the frame inputted by the frame input means 117. Further, in the immediately preceding frame, the area information which is referred to at the time of motion estimation is outputted to the referred area memory means 410.

[0123] The referred area data is shown in FIG. 18. The referred area data is the data in which the referred degree of each area is stored. ~~In the referred area data, the~~The referred degree of each area ~~means that, in pixels in the area, total pixel number which is~~is the total number of pixels referred to at the time of motion estimation from the next frame~~, is shown, and in FIG. 18, it is defined that the thicker the color of the area is, the higher the referred degree is.~~ In Fig. 18, the dark shading indicates a more highly referred degree.

[0124] The referred area memory means 410 stores the referred area inputted from the motion compensation means 403, and outputs the referred area data showing the referred area to the rate correction area selection means 412.

[0125] The rate correction area selection means 412 selects, in the inputted referred area data, a predetermined number of areas in the order from the area in which the referred area is low, as the rate correction data area. Further, the selected area is the rate correction area in the preceding frame immediately preceding the by one frame to the frame currently inputted by the frame input means[[, and]]. It outputs the rate correction area data 1201, showing the selected rate correction area, to the compression frame buffer 112 and the moving picture data combination means 414. Further, theThe operation of the compression frame buffer 112, quantization means 111, and variable length coding means 113 is the same as in Embodiment 1.

[0126] The compression frame combination means 414 combines the normal frame data inputted from the variable coding means 405, the rate correction area data inputted from the rate correction area selection means 412, and the rate correction data inputted from the variable length coding means 113 as shown in FIG. 13, and outputs it to the output means 115. In the present embodiment, because it is not conducted that the reference inhibition area is not set at the time of motion estimation and the search area is limited, as shown in Embodiments 1 and 2, the search area is not limited, and the predictive coding effect can be more enhanced than in Embodiments 1 and 2.

[0127] By using the coded moving picture data as an input as described above, and the moving picture coding apparatus in FIG. 2, when the new moving picture data is produced in the same manner as in Embodiment 1, the rate control can be quickly conducted without decoding the data. Further, because, as the area having the rate correction data, the area to which the referred degree is low at the time of motion estimation, is selected, even when the rate correction data is selected at the time of the rate control, the motion compensation error is not ~~caused~~created. Further, the number of area to be selected in the order from the area in which the referred degree is lower, can be determined by the user corresponding to the range of the bit rate change. Further, the number of rate correction data and the quantization value in respective areas also contribute to the width of the bit rate change.

[0128] For example, when the quantization of the normal frame data (size: CIF, frame rate 30 fps) is conducted at Q=24, the bit rate is about 100 kbps. In contrast ~~to this~~, the area [[in]]which ~~the referred degree is low and the~~has a likelihood of being referred to and whose size is the total [[of]] about 30% ~~in the~~ ~~area ratio~~of the frame (area ratio), is defined as the rate correction data area, and to respective areas, the quantization is conducted at two quantization values of Q=16 and 32[[, and the]]. The rate correction data having the bit rate corresponding to about 128 kbps and about 32 kbps is produced. With the moving picture data having this rate correction data, when the rate correction data is combined, the bit rate can be arbitrarily changed between about 128 and

about 64 kbps[[,]]. Accordingly, the moving picture data corresponding to the fluctuation of the band of the transmission path can be quickly produced. Further, the calculation cost according to the bit rate change is low, and a plurality of moving picture data whose bit rate are different, can be quickly produced. Further, the data size of the moving picture data is about 128 kbps, and it is almost equal to the maximum value of the bit rate change. In this example, the range of the bit rate change is smaller than in Embodiment 1[[, however]]. However, because the reference inhibition area is not provided, the lowering of the coding efficiency can be prevented, and because the area having the rate correction data is an area to which the practical referred degree is low, the generation of the motion compensation error which accompanies the replacement of the data can be suppressed to smallminimized.

[0129] As described above, [[in]] the present embodiment[[, the]] provides a moving picture data structure having the rate correction data [[to]]for the area [[to]]in which the referred degree is low at the time of motion estimation, and the. Further provided is a moving picture data producing apparatus which selects the rate correction data and changes the bit rate, are provided, and thereby. Accordingly, because the predictive coding efficiency of the motion estimation is not loweredreduced, and the motion compensation error generated when the rate correction data is used is lowered, and the rate control can be quickly conducted, a plurality of moving picture data whose bit rates are different, can be quickly produced, and its practical effect is large.

[0130] Embodiment 4

[0131] ~~In the~~The fourth embodiment[[, in]]_is_ an apparatus [[by]]_in_ which [[the]] previously coded moving picture data is not decoded, and the rate control is conducted, and the new moving picture data is produced~~, the apparatus characterized in that~~. In this embodiment, discussed below, the input moving picture data has the rate correction data whose bit ~~amount is~~_with_ slightly different bit amounts, [[on]]_for_ the entire frame~~, will be described below~~.

[0132] ~~In FIG. 5, the~~_Fig. 5 shows the_ structure of the moving ~~pictured at~~ a_picture data_ producing apparatus _501_ [[by]]_in_ which ~~the~~ coding is ~~previously~~ conducted for the input data [[of]]_to_ the moving picture coding apparatus ~~to conduct the rate control, is shown.__The moving picture coding apparatus performs rate control on the input data._ In FIG. 5, the moving data producing apparatus 501 is provided with: the frame input means 117 connected to the input means 116; motion compensation means 102; DCT conversion means 103; quantization means 104; ~~and~~variable length coding means 105~~, and is provided with the~~; inverse quantization means 106 for conducting the decoding; inverse DCT conversion means 107; and frame memory 108. Further, the moving picture coding apparatus 501 is provided with: a low pass filter 503 connected to the frame input means 117; motion compensation means 102 connected to the low pass filter 503; DCT conversion means 103; quantization means 104; and variable length coding means ~~106, and is provided with: the~~_105_; inverse quantization means 106 which is connected to the quantization means 104 and

conducts the decoding; inverse DCT conversion means 107; and frame memory

108. Further, ~~the moving picture data producing apparatus 501 is structured in~~

~~such a manner that it is connected to the variable length coding means 105, the~~

~~compression frame data combination means 504 connected to the variable~~

~~length coding means 105, and output means 115~~ included are a compression

frame data combination means 504 connected to the output means 115 and both

variable length coding means 105.

[0133] The operation of thus structured moving picture data producing

apparatus will be described below. In the moving picture coding apparatus 501,

~~teh~~the frame input means 117, motion compensation means 102, DCT

conversion means 103, quantization means 104, variable length coding means

105, inverse quantization means 106, ~~invesr~~inverse DCT conversion means 107,

and frame memory 108 are blocks for producing the normal frame data in the

same manner as in Embodiment 1.

[0134] Further, in FIG. 5, the low pass filter 503 causes the ~~non-~~

~~compression~~non-compressed frame to pass through the low pass filter 503,

reduces the high frequency information of the input frame, and outputs it to the

motion compensation means 102. Hereinafter, by using the DCT conversion

means 103, quantization means 104, variable length coding means [[506]]105,

inverse quantization means 106, inverse DCT conversion means 107, and frame

memory 108, in the same manner as in the normal frame data production, by

using the same quantization value, the frame data is produced. In this

connection, the frame data ~~produced herein is the data produced in such a~~ ~~manner that the data in which the high frequency of the input frame is reduced~~ ~~by~~that passes through the low pass filter 503[[,]] is coded, and is the data in which its bit amount is ~~fewer~~less than the normal frame data~~, and has the~~ ~~structure in which it has the correction data to~~. Furthermore, this data is structured to contain the correction data for the whole area ~~in 1~~of one frame shown in FIG. 10, and this data is called the rate correction data. The variable length coding means [[506]]105 calculates[[, to]] the rate correction data[[,]] header for the rate correction data ~~header~~ as shown in FIG. 20, and outputs the rate correction data and the rate correction data header to the ~~moving picture~~ ~~combination~~compression frame data combination means 20. The rate correction data header has the structure having the number of areas in the rate correction data [[1]]for one frame[[,]] and the bit amount in each area.

[0135] The compression frame data combination means 504 combines the normal frame data inputted from the variable length coding means 105, rate correction data header inputted from the variable length coding means 506, and rate correction data as shown in FIG. 19, and outputs it to the output means 115.

[0136] ~~As described above, in the present embodiment, the structure having~~ ~~the rate correction data is applied to all areas of 1 frame, and respective data~~ ~~amounts of the normal frame outputted from the variable length coding means~~ ~~105, and the rate correction data outputted from the variable length coding~~ ~~means 106, are slightly different, by reducing the high frequency component of~~

~~the non-compression frame.~~As described above, in the present embodiment, rate correction data is structured to have the rate correction data for all areas of one frame. The rate correction data is outputted from the variable length coding means 105. Corresponding normal frame data is outputted from the variable length coding means 105. The rate correction data and normal frame data are slightly different due to the reduced high frequency component of the non-compressed frame.

[0137] The structure of the moving picture coding apparatus2101, in which [[the]]new moving picture data ~~coded as described above is an input, and the rate control is conducted without decoding the data, and the moving picture data is newly~~is produced, is shown in FIG. 21. Moving picture data coded as described above is an input to the moving picture coding apparatus 2102. It performs rate control without decoding the data. In FIG. 21, the moving picture coding apparatus 2101 is provided with: the data separation means 207 connected to the input means 202; bit amount calculation means 203; rate correction data selection means 2104; bit rate control means 205; ~~and~~moving picture data combination means 208~~, and the apparatus has the structure in which these are connected to the~~; and an output means 206.

[0138] ~~The operation of thus structured moving picture coding apparatus 2101 will be described below. In FIG. 21, the operations of blocks other than the rate correction data selection means 2104 are entirely the same as in Embodiment 1. The rate correction data selection means 2104 conducts, by using the bit rate~~

~~error inputted from the bit rate control means 205, rate correction data header~~

~~inputted from the data separation means 207, rate correction data, and normal~~

~~frame data inputted from the bit amount calculation means 203, the rate control~~

~~so that the bit rate error is reduced. A flow of the processing of the rate control is~~

~~shown in FIG. 22.~~The operation of the moving picture coding apparatus 2101 will

be described below.   In FIG. 21, the operations of blocks other than the rate

correction data selection means 2104 are the same as in Embodiment 1.   The

rate correction data selection means 2104 performs the rate control which

reduces the bit rate error.   It does this by using the bit rate error inputted from the

bit rate control means 205, rate correction data header inputted from the data

separation means 207, rate correction data, and normal frame data inputted from

the bit amount calculation means 203.   A flow chart of the processing of the rate

control is shown in FIG. 22.

[0139] As shown in FIG. 22[[,]]:

[0140] STEP 1: ~~initially, the positive or negative of the bit rate error is judged,~~

~~and when it is negative or zero, the sequence is completed, and when it is~~

~~positive, that is, bit is excessive,~~Determine whether the bit rate error is positive or

negative. When it is negative or zero, the sequence is completed.   When it is

positive, the bit rate error is excessive.

[0141] STEP 2: [[the]]The rate correction data header is referred to, and the

maximum area of the bit amount is selected.

[0142] STEP 3: ~~to the selected area, the normal frame data is replaced with the rate correction data,~~Replace the normal frame data with the rate correction data for the selected area.

[0143] STEP 4: ~~after~~After the data is replaced, the bit rate error is renewed, and the sequence ~~advances~~proceeds to the bit rate error judgement process (STEP 1).

[0144] The above processing is repeated until the bit rate error becomes negative or zero, and when the processing is completed, the frame data is outputted to the moving picture data combination means 208. The moving picture data combination means 208 connects the frame data inputted for each [[1]]single frame in order, and the moving picture data is produced, and outputted to the output means 206.

[0145] In the present embodiment, after the rate correction data passes through the low pass filter, because it is quantized at the same quantization value as the normal frame, there is only a ~~little~~small difference in the bit amount, as compared to the normal data which is coded without a low pass filter, and by selecting the rate correction data to a plurality of areas, [[the]] fine rate control can be conducted.

[0146] The frequency characteristic of this low pass filter can be determined by the user corresponding to the range of the bit rate change. For example, ~~in the case where~~when the low pass filter ~~having the~~has a frequency characteristic ~~in which~~such that the coding data after [[the]] passage ~~of the low pass~~through the

filter is 64 kbps, and the filter is used ~~to the~~for moving picture data in which the bit rate after the coding is 128 kbps, when the input data is 128 kbps, [[the]] moving picture data ~~in which the fine bit rate change is possible in the range between 128 kbps and about 64 kbps,~~ can be produced in which fine bit rate change is possible in the range between 128kbps and about 64 kbps. Further, the calculation cost which accompanies the bit rate change is low, and ~~thereby~~therefore, a plurality of moving picture data whose bit rates are different, can be quickly produced.

[0147] Further, because the difference of the image quality in the rate correction data and the normal data are small as compared to the case where the image data is produced by changing the quantization value as in Embodiments 1, 2 and 3, the present embodiment is characterized in that the motion compensation error caused by selecting the rate correction data is small.

[0148] ~~As described above, in the present embodiment, to the whole areas in the frame, the moving picture data structure having together the rate correction data which is produced by removing the high frequency and being coded, and the moving picture coding apparatus by which the rate correction data is selected corresponding to the objective bit rate, and the rate control is conducted, are provided, thereby, because, while the motion compensation error is reduced, the fine rate control can be quickly conducted, a plurality of moving picture data whose bit rates are different, can be quickly produced, and its practical effect is large.~~As described above, the present embodiment provides, for the whole areas

in the frame, a moving picture data structure which includes the rate correction data.   The rate correction data is created by removing the high frequency component and coding.   The present embodiment further includes the moving picture coding apparatus which conducts rate control by selecting the rate correction data according to the desired bit rate.   In this embodiment, motion compensation error is reduced, fine rate control is conducted, and a plurality of moving picture data whose bit rates are different can be quickly produced.

[0149] Embodiment 5

[0150] ~~In the fifth embodiment, in the apparatus by which the rate control is conducted from the previously coded moving picture data, without decoding the data, and the moving picture data is newly produced, the apparatus characterized in that the input moving picture data has the data structure in which the bit reduction is possible at the time of rate control, will be described below. The present apparatus is structured by 2 apparatus of the moving picture data producing apparatus in which the moving picture data is previously coded, and the moving picture coding apparatus in which the rate control is conducted, and the moving picture data is produced.~~ The fifth embodiment is described below.   It performs rate control on previously coded moving picture data without decoding the data, and produces new moving picture data.   The apparatus is characterized in that the input moving picture data is structured such that bit reduction is possible at the time of rate control.   The present apparatus is structured by two apparatuses, which are the moving picture data producing apparatus in which the

moving picture data is previously coded, and the moving picture coding apparatus in which the rate control is conducted and the moving picture data is produced.

[0151] ~~Initially, the moving picture data producing apparatus by which the moving picture data having the structure in which the bit reduction is possible at the time of rate control, is produced, will be described, and next, the moving picture coding apparatus by which the rate control is conducted and the moving picture data is produced, will be described.~~Initially described below is the moving picture data producing apparatus for producing moving picture data structured for bit reduction at the time of rate control. Next, the moving picture coding apparatus for performing rate control and producing moving picture data will be described.

[0152] In FIG. 6, the structure of the moving picture data producing apparatus 601 is shown. ~~In FIG. 6, a~~The moving picture data producing apparatus 601 ~~is provided with~~includes: a moving picture coding means 603 connected to an input means 602; a data ~~dividing~~division position selection means 605 for selecting the dividable position in the data of the ~~Video Packet~~video packet structured by a continuous arbitrary number of macro blocks; video ~~Packet~~packet termination data producing means 606; ~~and~~rate correction data producing means 607 for storing the information for the rate correction~~, and is provided with moving picture data combination means 608 connected to the Video Packet producing means 604~~; compression frame data combination means 608 connected to the moving

picture coding means 603 and the rate correction data producing means 607,
and has the structure in which these are connected to; and an output means 609.

[0153] The operation of the moving picture data producing apparatus 601
structured as above will beis described below. Initially, the input means 602
inputs the non-compressionnon-compressed image into the moving picture
coding means 603 for each [[1]] frame. Then, the moving picture coding means
603 conducts the motion compensation, DCT conversion, quantization, and
variable length coding processing on the inputted frame in the Video Packetvideo
packet unit structured by the continuous arbitrary macro block. Further, the
moving picture coding means 603 stores respective start positions of the final
macro block for each Video Packetvideo packet at the time of the coding, and
produces the Video Packetvideo packet structure data. The Video Packetvideo
packet structure data is shown in FIG. 36. In FIG. 36, the Video Packetvideo
packet structure data records the total number of the Video Packetvideo packet,
and the start position of the final macro block in respective Video Packetsvideo
packets.

[0154] Then, the moving picture coding means 603 outputs the coded Video
Packetvideo packet to the data dividing position selection means 605 and the
movingcompression frame data combination means 608, and outputs the Video
Packetvideo packet structure data to the data dividingdivision position selection
means 605. Herein, the Video Packetvideo packet may have the same structure
as in the area shown in, for example, FIG. 10, but, it is necessary that each

~~Video Packet~~video packet is structured by the continuous macro blocks in the lateral direction.

[0155] The data ~~dividing~~division position selection means 605 selects the area which can be deleted at the time of rate control for the respective final macro blocks of the inputted ~~Video Packet~~video packet, and determines its border as the dividing position of the ~~Video Packet~~video packet. In each ~~Video Packet~~video packet, the continuous macro block is accommodated in order~~, and in.~~ In each macro block, ~~because~~ the variable length ~~sign~~code of the quantized DCT coefficient is accommodated in order from the low frequency side. Accordingly, in the final macro block of the ~~Video Packet~~video packet, the variable length ~~sign~~code of the rear side corresponds to the high frequency DCT coefficient ~~of the high frequency~~. Accordingly, as shown in FIG. 23, the final macro block of the ~~Video Packet~~video packet is divided at the time of rate control, and the position to delete the subsequent data is selected from the rear side of the final macro block of each ~~Video Packet~~video packet. That is, the data ~~dividing~~division position selection means 605 causes the high frequency DCT coefficient ~~of the high frequency accommodated in~~located at the rear side of the final macro block of the ~~Video Packet~~video packet to be the area which can be deleted. Further, because the high frequency component ~~is smaller, as compared to~~has a smaller influence on the image quality than the low frequency component, ~~in the influence onto the image quality~~ even when the information is deleted, the deterioration of the image quality by deleting the high frequency component is

small. Then, the data ~~dividing~~division position selection means 605 outputs the information of the selected position[[,]] and [[its]]the bit amount ~~and the~~ subsequent to the selected position and the bit amount subsequent to the selected position to the rate correction data producing means 607, and outputs the information of the selected position and each ~~Video Packet~~video packet to the ~~Video Packet~~video packet termination data producing means 606.

[0156] ~~The Video Packet termination data producing means 606 calculates, to the first variable length sign beginning from the position selected by the data dividing position selection means 605, the variable length sign when the sign is the last of the Video Packet, and further, as shown in FIG. 24, produces the Video Packet termination data to which the stuffing bit for byte alignment when it is the last of the Video Packet, is added, and outputs it to the rate correction data producing means 607. Herein, the Video Packet termination data itself is also added by the stuffing bit for adjusting the byte alignment. Then, the rate correction data producing means 607 collects the divided position inputted by the data dividing position selection means 605, the bit amounts subsequent to the position, the Video Packet termination data inputted by the Video Packet termination data producing means 606, as the rate correction data, and output it to the compression frame data combination means 608. FIG. 25 is a view showing the rate correction data structure and rate correction data header structure in the present fifth embodiment. Further, FIG. 26 is a view showing the data content of the rate correction data shown in FIG. 25. The rate correction~~

~~data has the structure, as shown in FIG. 25 and FIG. 26, consisting of the rate correction data header, and a plurality of Video Packet termination data, and the rate correction data header has the structure including the Video Packet number of 1 frame, bit number showing the divided position of each Video packet, bit amounts which can be deleted, subsequent to the divided position, and bit amount of the Video Packet termination data.~~The video packet termination data producing means 606 calculates a variable length code for a first variable length code starting from a position selected by the data division position selection means 605 when the code is the last of the video packet. Further, as shown in FIG. 24, the video packet termination data producing means 606 produces the video packet termination data to which the stuffing bit for byte alignment when it is the last of the video packet, is added, and outputs it to the rate correction data producing means 607. Herein, the stuffing bit is also added to the video packet termination data for adjusting the byte alignment. Then, the rate correction data producing means 607 collects the following as the rate correction data: the divided position inputted by the data division position selection means 605, the bit amounts subsequent to the position, and the video packet termination data inputted by the video packet termination data producing means 606. The rate correction data is then outputted to the compression frame data combination means 608. FIG. 25 is a view showing the rate correction data structure and rate correction data header structure in the present fifth embodiment. Further, FIG. 26 is a view showing the data content of the rate correction data shown in FIG.

25. The rate correction data is comprised of the rate correction data header, and a plurality of video packet termination data. The rate correction data header includes the video packet number of a frame, bit number showing the divided position of each video packet, bit amounts subsequent to the divided position which can be deleted, and bit amount of the video packet termination data.

[0157] Finally, the moving picture datacompression frame data combination means 608 combines the normal Video Packetvideo packet inputted by the Video Packet producing means 604moving picture coding means 603 for each [[1]] frame, and the rate correction data inputted by the rate correction data producing means 607 for each [[1]] frame, in order, and produces the moving picture data, and outputs it to the output means 609.

[0158] Next, the moving picture coding apparatus will be described. The moving picture coding apparatuswhich conducts the rate control and produces the moving picture data. Its input is from the moving picture data produced by the moving picture data producing means, will be described apparatus 601.

[0159] The structure of the moving picture coding apparatus 701 is shown in FIG. 7. In FIG. 7, the moving picture producing apparatus 701 hasIt includes a rate correction data extraction means 703 connected to an input means 702[[,]]; data composition means 704[[, and]]; rate correction means 706[[, and]]; a bit rate control means 705 connected to the input means 702, rate correction data extraction means 703, and data composition means 704, and has the structure connected to; and an output means 707. The operation of the structured as

described above, will be described below. The moving picture producing apparatus 701 has the moving picture data outputted by the output means 609 as an input, and conducts the rate change and newly produces the moving picture data. The operation of the moving picture coding apparatus 701 is described below. The input to the moving picture coding apparatus 701 is the output from the moving picture data producing apparatus 601 provided at the output means 609. The moving picture coding apparatus 701 performs the rate change and produces new moving picture data.

[0160] The input means 702 inputs the coded moving picture data, including the Video Packetvideo packet for each [[1]] frame, to the rate correction data extraction means 703, and the objective. It also inputs the desired bit rate into the bit rate control means 705. The rate correction data extraction means 703 extracts the rate correction data from the inputted moving picture data[[,]] and outputs it to the bit rate control means 706, and705. The rate correction data extraction means 703 also outputs the normal Video Packet other than the rate correction data tovideo packet (excluding the rate correction data) to the data composition means 704. The data composition means 704 combines the inputted Video Packetsvideo packets and composes the frame data, [[and]] outputs the generated bit amount to the bit rate control means 705, and outputs the composite frame data to the rate correction means 706. Further, theThe bit rate control means 705 compares the objectivedesired bit rate inputted from the input means 702 to the generated bit amount inputted from the data composition

means 704, and calculates the bit rate error[[, and to]]. To satisfy the objectivedesired bit rate, when the bit amount is excessive, the bit rate control means 705 refers to the rate correction data header in the rate correction data inputted from the rate correction data extraction means 703, and selects from which position Video Packet the bit isvideo packets the bits are deleted[[, and]]. The bit rate control means 705 outputs the correction data corresponding to the rate correction data header showing the position, to the rate correction means 706. Herein, the selection method of the Video Packetvideo packet to delete the bits, is as follows: the Video Packetvideo packet is selected in the order of the Video Packet in which the bit amount to be deleted in the rate correction data header is larger, and the bit is deleted, and the bit amount which can be deleted, is the differentiated from the bit rate error, and by adding the bit amount of the termination data, the bit rate error is renewed, and thedescending order according to the amount of bits to be deleted in the rate correction data header, the bits are deleted, the bit amount which can be deleted is subtracted from the bit rate error, and to this is added bit amount of the termination data, which updates the bit rate error. The selection processing is continued until the objective bit rate is satisfied.

[0161] The rate correction means 706 deletes the bits subsequent to the bit position which can be deleted, accommodated in the rate correction data header, for the Video Packetvideo packet inputted by the bit rate control means 705, and the. The Video Packetvideo packet termination data inputted by the rate control

means 706 is inserted instead of them, and thereplaces the deleted bits. The frame data which is rate corrected, is outputted to the output means 707. The output means 707 composessynthesizes the moving picture data, inputted for each 1 frame from the rate correction means 706, for each frame and produces the moving picture data.

[0162] As described above, to deletedeleting the rear portion bits of the final macro block of the Video Packetvideo packet so that rate correction is conducted[[,]] is equivalent to thatremoving the high frequency component of the final macro block of the Video Packetvideo packet. is removed, and has the same effect as a case that the variable length decoding and re-quantization are conducted Accordingly, this process has the same effect as the process in which the variable length decoding and re-quantization are conducted, and the bit rate is lowered. Further, becauseBecause the decoding processing is not necessary, the processing is light and the rate control can be quickly conducted.

[0163] Further, the number of the rate correction data is equal to the number of the Video Packetvideo packet, and the number of the Video Packetvideo packet can be set by the user corresponding to the range of the bit rate change. For example, in the case where the size of [[1]]one Video Packetvideo packet is small, for example, several [[%]]percent of the whole frame, which is small, and the data amount of the rear portion bit which can be deleted, corresponds to about 10% [[to]]of the data amount of 1 Video Packetone video packet, when the input data is about 64 kbps, the data in which the bit rate can be changed in the

range of about 64 kbps to about 56 kbps, can be produced. Thereby, in order to cope with the fluctuation of the network, the bit rate change can be quickly conducted. Further, the present embodiment is characterized in that the rate correction data may be smaller, as compared to Embodiments 1 to 4.

[0164] As described above, [[in]] the present embodiment[[,]] provides: the ~~Video Packet~~video packet structure whose rear portion bit can be deleted, the moving picture data structure having the rate correction data in which the position information and termination data are stored, and the moving picture coding apparatus which refers to the rate correction data and deletes the bits of rear portion of the ~~Video Packet~~video packet and conducts the rate control, are provided, thereby. Accordingly, the rate control can be quickly conducted without decoding the moving picture data, and its practical effect is large.

[0165] Embodiment 6

[0166] ~~In the sixth embodiment, in the moving picture coding apparatus in which the rate control is conducted from the previously coded moving picture data without decoding the data and the moving picture data is newly produced, the moving picture coding apparatus characterized in that the input moving picture data has, as the rate correction data, the structure having the I-frame which is the coded image in the frame whose bit amount is different to the normal frame, will be described below. Initially, the moving picture data producing apparatus in which the moving picture data which is an input of the moving picture coding apparatus, is produced, will be described, and next, the moving~~

~~picture coding apparatus by which, from the moving picture data coded by the moving picture data producing apparatus, the rate control is conducted without decoding the data, and the moving picture data is newly produced, will be described below.~~The sixth embodiment will be described below. It includes a moving picture coding apparatus for performing rate control without decoding on previously coded moving picture data, and for producing new moving picture data. The moving picture coding apparatus has moving picture data as an input. The input moving picture data is structured so that the I-frame, which is the coded image in the frame whose bit amount is different to the normal frame, is the rate correction data. The moving picture data producing apparatus and the moving picture coding apparatus will be described below.

[0167] The moving picture data producing apparatus produces moving picture data, which is inputted to the moving picture coding apparatus. In FIG. 8, the structure of the moving picture data producing apparatus 801 ~~to produce the input moving picture data of the moving picture coding apparatus~~ is shown. ~~The moving picture data producing apparatus 801 is provided with~~It includes the following: a frame input means 808 connected to the input means 802[[,]]; a P-frame coding means 803[[, and]]; a bit amount buffer 804~~, and is provided with a frame input means 808, and~~; an I-frame coding means 805 connected to the bit amount buffer 804~~, and further, is provided with a~~, frame input means 808, and compression frame data combination means 809; the compression frame data combination means 809 is connected to the P-frame coding means 803~~and~~, the

I-frame coding means 805, and a moving picture data combination means 806, and has the structure connected to an output means 807.

[0168] The operation of the moving picture data producing means structured as described above801 will be described below. The frame input means 808 inputs the non-compressionnon-compressed image into the P-frame coding means 803 and I-frame coding means 805 for each [[1]]single frame. The P-frame coding means conducts the P-frame coding through the motion compensation, DCT conversion, quantization, and variable length coding processing, and outputs the coded frame to the compression frame data combination means 809, and outputs the bit amount of the coded frame to the bit amount buffer 804. The bit amount buffer 804 outputs the inputted bit amount to the I-frame coding means 805.

[0169] Then, the I-frame coding means 805 conducts the I-frame coding through the DCT conversion, quantization, and variable length coding processing, on the frame inputted from the input means 802, and outputs the coded frame to the compression frame data combination means 809. Herein, theThe detailed structure of the I-frame coding means 805 is shown in FIG. 37. In FIG. 37, the I-frame coding means 805 is connected to an input means 3701, and is structured byincludes the following: a DCT conversion means 3702[[,]]; DCT coefficient memory 3703[[,]]; quantization means 3704[[,]]; variable length coding means 3705[[,]]; and quantization value determination means 3706[[,]]; and is connected to an output means 3707. In FIG. 37, theThe input means 3701

corresponds to the output of the frame input means 808 in FIG. 8, and the output of the bit amount buffer 804, and inputs the non-compressionnon-compressed frame into the DCT conversion means 3702[[,]] and inputs the bit amount into the quantization value determination means 3706. The DCT conversion means 3702 DCT-converts the inputted non-compressionnon-compressed data, and outputs it to a DCT coefficient memory 3703. The DCT coefficient memory 3703 stores the inputted DCT coefficient in the internal memory, and inputsoutputs the DCT coefficient into a quantization means 3704. Further, when the DCT coefficient signal is inputted from the quantization value determination means 3706, the DCT coefficient stored in the internal memory is outputted to the quantization means 3704. The quantization means 3704 conducts the quantization by using the DCT coefficient inputted from the quantizatioDCT coefficient memory[[,]] 3703 and the quantization value inputted from the quantization value determination means 3706, and outputs it to the variable length coding means 3705. The variable length coding means 3705 conducts the variable length coding on the inputted data, and outputs the variable length coding data and its bit amount to the output means 3707, and the. In addition it outputs the bit amount to the quantization value determination means 3706.

[0170] The quantization value determination means 3706 stores the bit amount inputted from the input means 3701 in the internal memory, and outputs the previously determined quantization value to the quantization means 3704. Further, when the bit amount is inputted from the variable length coding means

3705, it is compared to the bit amount stored in the internal memory, and the next quantization value is determined so that the bit amount becomes small, and the. The quantization value is outputteddetermination means 3706 outputs the quantization value to the quantization means 3704[[,]] and the DCT coefficient output signal is outputted to the DCT coefficient memory 3703. Further, by using the bit amount inputted from the variable length coding means 3705, the internal memory is renewedupdated.

[0171] After the above processings are is repeated [[by]]for the number of times [[of]]as there are pieces of the rate correction data which is previously determined by the user, the quantization value determination means 3706 outputs the I-frame coding end signal to the output means 3707.

[0172] As described above, the I-frame coding means 805 produces a plurality of I-frames whose bit amount is different from the inputted bit amount, and outputs the produced I-frame and its bit amount to the compression frame data combination means 809. Finally, the compression frame data combination means 809 combines the P-frame data inputted from the P-frame coding means 803, and the rate correction data produced from a plurality of I-frame data and their bit amounts inputted from the I-frame coding means 805, in order, and outputs it to the output means 807. FIG. 27 is a view showing the rate correction data structure and the rate correction data header structure in the present sixth embodiment. Further, FIG. 28 is a view showing the data content of the rate correction data shown in FIG. 27. The rate correction data is, asAs shown in FIG.

27 and FIG. 28, the rate correction data is comprised ofstructured by the rate correction data header and a plurality of I-frames. The rate correction data header has the structure in whichis structured such that the number of I-frames and respective bit amounts are accommodated in the fixed length.

[0173] Next, the structure of the moving picture coding apparatus is shown in Fig. 9. in which the moving picture data coded by the moving picture data producing apparatus 801 is an input, and the rate control is conducted without coding, and the moving picture data is newly produced, is shown in FIG. 9. The moving picture coding apparatus 901 has the structure which is provided withincludes the following: a rate correction data extraction means connected to an input means 902 and; a bit rate control means 905 connected to the input means 902 and the rate correction data extraction means, and further,; a rate correction means 906 connected to [[a]]the bit rate control means 905, and the rate correction data extraction means 903, and is connected to; and an output means 907.

[0174] The operation of the moving picture coding apparatus structured as described above,901 will be described below. The input means 902 inputs the moving picture data coded by the moving picture data producing means 801 for each [[1]]single frame[[,]] into the rate correction data extraction means 903, and. It also inputs the objectivedesired bit rate into the bit rate control means 905. The rate correction data extraction means 903 extracts the rate correction data from the inputted data and outputs it to the bit rate control means 905, and. It also

outputs the normal P-frame data ~~other than the rate correction data to~~(excluding the rate correction data) to the rate correction means 906~~, and~~. It further outputs the bit amount of the P-frame to the bit rate control means 905.

[0175] Then, the bit rate control means 905 compares the ~~objective~~desired bit rate inputted from the input means 902, to the bit amount inputted from the rate correction data extraction means 903~~, and when~~. When the bit rate is satisfied, and the immediately preceding frame ~~which is preceding 1 frame~~ is not frame-skipped, the control signal in which the rate correction is not necessary[[,]] is outputted to the rate correction means 906. In contrast to that, when the bit rate is not satisfied, or the immediately preceding frame which is ~~preceding 1 frame is~~ frame-skipped, the rate correction data header is referred to, and from I-frames ~~in the rate correction data, the I-frame~~ which satisfies the ~~objective~~desired bit rate is selected~~, and the~~. The selected I-frame is then outputted to the rate correction means [[706]]906. Further, even when the rate correction data is used, when the bit amount is excessive, the frame skip control signal is outputted to the rate correction means 906, and the information whether the frame skip control signal is emitted[[,]] is stored in the internal memory.

[0176] ~~Further, when the control signal of the rate correction unnecessary is inputted from the bit rate control means 905, the rate correction means 906 outputs the frame inputted from the rate correction data extraction means 903 as it is, to the output means 907, and when the I frame is inputted from the bit rate control means 905, the I frame is outputted to the output means 907, and when~~

~~the frame skip control signal is inputted from the bit rate control means 905, the frame skip control signal is outputted to the output means 907. Finally, the output means 907 collects the frame data inputted from the rate correction means 906 for each 1 frame, and frame skip control signal, and the moving picture data is produced. In this connection, when the frame skip control signal is inputted, the frame is skipped.~~Further, when the control signal in which the rate correction is not necessary is inputted from the bit rate control means 905, the rate correction means 906 outputs, to the output means 907, the frame inputted from the rate correction data extraction means 903 unchanged. When the I-frame is inputted from the bit rate control means 905, the I-frame is outputted to the output means 907. When the frame skip control signal is inputted from the bit rate control means 905, the frame skip control signal is outputted to the output means 907. Finally, the output means 907 collects the frame data inputted from the rate correction means 906 for each frame, and frame skip control signal, and the moving picture data is produced. In this connection, when the frame skip control signal is inputted, the frame is skipped.

[0177] In the present embodiment, ~~because the input moving picture data has the I frame as the rate correction data~~the generation of motion compensation error can be prevented, even when the frame skip is conducted at the time of rate control, by using the I-frame for the next frame~~, the generation of the motion compensation error can be prevented~~. This is because the input moving picture data has the I-frame as the rate correction data.

[0178] Further, the number of pieces of the I-frame which is the rate correction data, and the quantization value when the rate correction data is produced, can be set by the user corresponding to the range of the bit rate change. ~~Foe~~For example, when the quantization of the normal frame data is conducted at the quantization value Q=2, and the bit rate is about 1.6 Mbps, the quantization is conducted by using 2 quantization values of Q=6, Q=29, as the rate correction data, and the data of about 384 kbps and about 64 kbps are produced. Then, by using together the rate correction data or frame skip, it is possible to produce ~~the~~ moving picture data ~~in which~~having the arbitrary bit rate change of range from about 1.6 Mbps to about 64 kbps ~~is possible, can be produced~~.

[0179] As described above, in the present embodiment, when the moving picture data producing apparatus has a means for producing the I-frame whose bit amount is different[[,]] as the rate correction data, and the moving picture coding apparatus is provided with~~, as the rate correction data,~~ a means for selecting the I-frame as the rate correction data and conducting the rate control, the rate control can be quickly conducted without decoding the input moving picture data~~, and further~~. Further, the generation of ~~the~~ motion compensation error when the frame-skip is conducted[[,]] can be prevented, and a plurality of moving picture data whose bit rates are different can be quickly produced~~, and its practical effect is large~~.

[0180] Embodiment 7

[0181] In the seventh embodiment, ~~in an apparatus by which the rate~~described below, rate control is conduced ~~from the~~on previously coded moving picture data without decoding the data[[,]] and ~~the~~new moving picture data is ~~newly~~produced[[,]]. This embodiment further includes a moving picture coding apparatus characterized in that a portion of the area in the frame of the moving picture data is selected and removed~~quarried out~~, and the frame size is different from the input moving picture data~~, and the~~. The moving picture data, whose size is the ~~quarried out~~selected and removed frame size, is produced[[,]] and will be described below. When the size is ~~quarried out~~selected and removed from the frame size of the input image data and the moving picture data is produced, ~~because~~the bit rate is not ~~uniform, the bit is not~~regulated depending on the ~~quarried out~~selected and removed portion because the bit rate is not uniform, and in order to ~~quarried out~~select and remove data, it is necessary that the bit rate [[is]]be changed.

[0182] ~~Initially, the moving picture data producing apparatus by which the moving picture data which is an input of the moving picture coding apparatus is produced, will be described, and next, the moving picture coding apparatus by which the rate control is conducted from the previously coded moving picture data without decoding the data, and the moving picture data is newly produced, will be described below.~~Initially, the moving picture data producing apparatus and moving picture coding apparatus will be described below. The moving picture data producing apparatus produces moving picture data, which is an input to the

moving picture coding apparatus. The moving picture coding apparatus performs rate control without decoding the input data and produces new moving picture data.

[0183] In FIG. 29, the structure of the moving picture data producing apparatus ~~to produce the input moving picture data of the moving picture coding apparatus~~2901 is shown. ~~In FIG. 29, a~~The moving picture data producing apparatus 2901 is provided with: a frame input means 117 connected to an input means 116; motion compensation means 2902; DCT conversion means 103; quantization means 104; variable length coding means 105; inverse quantization means 106 to conduct the decoding; inverse DCT conversion means 107; and frame memory 108 to store the decoded frame~~, and is provided with:~~; a maximum bit amount area detecting means 2910 to detect the area having the maximum bit amount, connected to the variable length coding means 105; reference inhibition area memory means 109; compression frame buffer 112 connected to the DCT conversion means 103; quantization means 2911 to conduct the quantization, connected to the compression frame buffer 112; ~~and~~ variable length coding means 2913, ~~and is provided with:~~ a compression frame data combination means 2914 to combine the moving picture data, connected to the variable length coding means 105, reference inhibition area memory means 109, ~~and~~variable length coding means 2913~~, and has the structure connected to;~~ and the output means 115. The operation of the moving picture data producing apparatus ~~structured as described above~~2901 will be described below. In FIG.

29, operations of the motion compensation means 2902, maximum bit amount area detecting means 2910, quantization means 2911, variable length coding means 2913, and the operation of the blocks other than compression frame data combination means 2914 are entirely the same as in the Embodiment 1.

[0184] An example of the ~~quarry out~~select and remove area is shown in FIG. 30. In FIG. 30, [[1]]a single frame is divided into 4 ~~quarry out~~select and remove areas surrounded by a bold line. The moving picture data produced by the moving picture data producing apparatus 2901~~means in the present embodiment~~ is different form the input frame size, and has the structure in which, for example, the moving picture data can be produced by the moving picture coding apparatus, which will be described later, as the frame size of an arbitrary select and remove area (quarry out area) shown in FIG. 30.

[0185] In the Embodiment 1, the maximum bit amount area detecting means 110 selects a plurality of areas in the order of bit amount from the ~~range including the~~ maximum ~~bit amount~~ in the plurality of areas in [[1]]a single frame shown in FIG. 10~~, and to the selected area, by~~. By changing the quantization value for the selected area by the quantization means 111, the rate correction data whose bit amount is different is produced.

[0186] In contrast to that, in the present embodiment, the maximum bit amount area detecting means 2910 selects, for example, as shown in FIG. 30, ~~to 1~~for a single frame which is divided into a plurality of select and remove areas (quarry out areas~~(rectangular area shown by a bold line~~) that are shown outlined

in bold, a plurality of areas in the order from the area in which the bit amount is maximum in each ~~quarry out~~select and remove out area, ~~and outputs the~~. Each selected ~~each~~out area is outputted to the reference inhibition area memory means 109, and to the compression frame buffer 112. In this connection, the ~~quarried out~~selected and removed area shown in FIG. 30 is an example[[,]] and ~~the quarry out area~~ can be arbitrarily determined. Further, the motion compensation means 2902 conducts the motion compensation by inhibiting the motion estimation to the reference inhibition area shown in the rate correction data ~~31~~inputted from the reference inhibition area memory means and the ~~quarry out~~select and remove area of the position which is different from the currently coded ~~quarry~~select and remove area. For example, when the motion compensation is conducted on ~~the quarry out~~select and remove area 1, the motion estimation is conducted only from the area ~~excepting for~~other than the reference inhibition area in the ~~quarry out~~select and remove area 1, in one preceding frame to the frame into which the input is conducted from the frame memory 108. Tentatively, when the motion estimation is conducted ~~to the~~for the area outside of the ~~quarry~~select and remove area, decoding cannot be conducted because, although moving picture data is produced, there is no reference image to be used for the motion compensation when the area is ~~quarried~~selected and removed from the inside of one frame ~~and the moving picture data is produced, the decoding can not be conducted~~. As described above, by providing the limitation for the motion estimation, the decoding of the

coded moving picture data can be conducted by using not only the whole frame, but also only each select and remove (quarry out) area, and the. Furthermore, the moving picture data can be structured by quarrying outselecting and removing a portion from the frame of the coded moving picture data.

[0187] The quantization means 2911 changes the quantization value and conducts the quantization by using. For this is uses the DCT coefficient and quantization value of each area selected by the reference inhibition area shown in the rate correction area data inputted from the compression frame buffer 112, that is, selected by the maximum bit amount area detecting means 2910, and produces the data. The quantization means 2911 produces the data whose bit amount is different, and respectively outputs to the variable length coding means 2913.

[0188] The variable length coding means 2913 conducts the variable length coding on the DCT coefficient whose bit amount is different[[, of]] for each reference inhibition area inputted by the quantization means 2911[[, and]]. The variable length coding means 2913 produces the rate correction data having respective data sizes and area numbers as the header information, and outputs it to the compression frame data combination means 114. Herein, the data produced by the variable length coding means 2913 is called the rate correction data. In FIG. 33, the structure of the rate correction data is shown. In FIG. 33, the rate correction data header 3302, as shown in FIG. 34, has the structure in which the number of the correction data in each area, the area number in the frame,

and the bit amounts of respective correction data, are accommodated as the fixed length data. Then, the rate correction data has theis structured in whichso that the correction data is accommodated in order succeeding tofollowing the rate correction data header 3302.

[0189] The compression frame data combination means 2914 links in order the normal frame data inputted by the variable length coding means 105, the rate correction area data inputted by the reference inhibition area memory means 109, and the rate correction data inputted by the variable length coding means 2913 as shown in FIG. 32, and. It produces the compression frame data, andwhich it outputs [[it]] to the output means 115.

[0190] Next, [[in]] FIG. 35[[,]] shows the structure of the moving picture coding apparatus 3501 by which a portion in the frame is quarriedselected and removed from the moving picture data coded by the moving picture coding apparatus in FIG. 29 without being coded, and the bit rate adjustment following the quarrying outselection and removal is conducted, and the new moving picture data is newly produced, is shown.

[0191] In FIG. 35, the moving picture coding apparatus 3501 has the structure which is provided with: a data separation means 3507 connected to an input means 3502; bit amount calculation means 2303203; rate correction data selection means 2404204; thee bit rate control means 205; and moving picture data combination means 208, and which is connected to the output means 206. The operation of the moving picture coding apparatus 3501structure as

~~described above~~ will be described below. In FIG. 35, the operations of blocks other than the input means 3502 and data separation means 3507, are ~~entirely~~ the same as in Embodiment 1.

[0192] ~~The input means 3502 inputs the moving picture data which is compression coded by the moving picture data producing means 2901, objective bit rate, quarry area information showing the quarry out method of 1 frame as shown in FIG. 30, and quarry out area number showing which portion of the input data is to be quarried out, to the data separation means 207. When the data is inputted into the data separation means 3507 by the input means 3502, the objective bit rate is inputted into the bit rate control means 205 for each 1 frame, and the data is taken out in order from the leading end of the inputted moving picture data, the quarrying out and composition is conducted on the normal frame data corresponding to the quarry out area number, and it is inputted into the bit amount calculation means 203 for each 1 frame, and the rate correction data corresponding to the rate correction area data and the quarry out area number is inputted into the rate correction data selection means 204.~~The input means 3502 inputs to the data separation means 3507 the moving picture data which is compression coded by the moving picture data producing means 2901, desired bit rate, select and remove (quarry out) area information showing the select and remove method for a single frame as shown in FIG. 30, and select and remove (quarry out) area number showing which portion of the input data is to be selected and removed. When the data is inputted into the data separation

means 3507, the desired bit rate is inputted into the bit rate control means 205 for each single frame. The data is taken out in order from the leading end of the inputted moving picture data and the quarrying out and construction is conducted on the normal frame data corresponding to the select and remove area number. This modified data is inputted into the bit amount calculation means 203 for each single frame, and the rate correction data corresponding to the rate correction area data and the select and remove (quarry out) area number is inputted into the rate correction data selection means 204.

[0193] ~~Generally, in the case where, to the previously coded image data, a portion of the frame is quarried out and the new moving picture data whose frame size is different, is produced, when the motion estimation is conducted from the area other than the area in which the previously coded image data is quarried out, the problem in which it can not be decoded, is generated. That is for the reason why the necessary reference data to decode the quarried out area does not exist inside the quarried out area. That is, because the necessary reference data exists outside the quarried out area, it is impossible that the quarrying out is simply conducted, and in order to quarry out a portion of the frame and produce the new moving picture data whose frame size is different, it is necessary that, after whole frame is decoded once, the inside of the quarry out area is coded again, and there is a problem that the processing load is large.~~ Generally, when previously coded image data is provided, and a portion of the frame is selected and removed, producing new moving picture data whose

frame size is different, motion estimation conducted from the area other than the area in which the previously coded image data is selected and removed is problematic because the data cannot be decoded. That is the reason for why the necessary reference data to decode the selected and removed area does not exist inside the selected and removed area. That is, because the necessary reference data exists outside the selected and removed area, it is not possible that the selection and removal is simply conducted. In order to select and remove a portion of the frame and produce the new moving picture data whose frame size is different, it is necessary that, after the whole frame is decoded once, the inside of the select and remove area is coded again. This extra coding is problematic in that the processing load is large.

[0194] In contrast to that, in the present embodiment, when the data separation means 3507 quarries out selects and removes the data of the area shown by the quarry out select and remove area number from the normal frame data, and composes the new frame whose frame size is different, because the motion estimation of the quarried selected and removed area is conducted only in the same area, there is no case that the motion compensation error is generated by the quarrying [[out]]and removing, and it can not be decoded. Accordingly, it can be quarried out selected and removed and composed without decoding the data. Further, also the change of bit rate following the quarrying out, selection and removal can be conducted without decoding the data by selecting the rate

correction data by adjusting to the ~~objective~~desired bit rate in the same manner as in Example 1.

[0195] Further, the number of areas having the rate correction data and the rate correction data of each area, can be set by the user corresponding to the range of the bit rate change, and has the same effect as in Embodiment 1~~,~~ ~~however.~~ However, the rate correction data necessary only for conducting the bit rate adjustment following the ~~quarrying out~~selection and removal may be small. For example, when ~~the quarry out~~there are four select and remove areas ~~are 4,~~ and the quantization value of the normal frame data Q=8, and the bit rate is about 256 kbps[[,]] as the rate correction data, at least one area in which the bit amount is large is selected in respective ~~quarry out~~select and remove areas~~, and~~ ~~when.~~ When the rate correction data of about 96 kbps (as the whole frame) in which the quantization is conducted by using the quantization value Q=20[[,]] is produced, it is ~~sufficiently enough~~sufficient enough for adjustment of the bit rate generated following the ~~quarry out~~selection and removal. That is, when ~~the~~ ~~quarry out areas is 4~~there are four select and remove areas, and the bit rate is about 256 kbps, it is necessary that the bit rate of the frame ~~quarried out by the~~ ~~quarry out of the area is~~selected and removed area be 1/4 of the whole, that is, about 64 kbps~~, however.~~ However, in practice, by the deviation of the bit amount, the area over 64 kbps exists. In the present embodiment, ~~the~~ rate correction data is produced~~, and by.~~ By using the rate correction data at the time

of ~~quarry out~~selection and removal of the area, the bit rate of such ~~the~~an area can be adjusted.

[0196] As described above, in the present embodiment[[,]] includes the moving picture data structure ~~having the~~with an area having the rate correction data in which the bit amount is different for each ~~quarry~~select and remove area, a. It further includes means by which the area of a portion in the frame is ~~quarried out and composed~~selected and removed and constructed, and an area selection means for selecting the rate correction data corresponding to the bit rate, ~~are provided, thereby~~. Thereby, a portion of the frame is quickly ~~quarried out~~selected and removed without decoding the moving picture data[[,]] and without generating the deterioration of image quality, ~~and further~~. Further, the bit rate adjustment can be conducted and the new moving picture data whose frame size is different, can be produced, ~~and its practical effect is large~~.

[0197] Further, in the present embodiment, when ~~a point that the~~an area having the reference inhibition area and rate correction data is produced ~~in 1~~for a single frame[[,]] is changed [[to]]so that it is produced for each ~~quarry out~~select and remove area~~s~~, and following that, also for the motion compensation, the motion estimation is not conducted ~~from the~~outside of the ~~quarry out~~select and remove area, ~~it is~~. It has been shown that ~~the effect in which, not only by conducting the rate control without decoding the coded moving picture data, but also by quarrying out a portion in the frame without decoding the data, the moving picture data whose frame size is different can be produced, can be~~

~~obtained, and for~~moving picture data whose frame size is different can be produced not only by conducting the rate control without decoding the coded moving picture data, but also by selecting and removing a portion in the frame without decoding the data. For Embodiment 2 to Embodiment 6, by conducting the same change, a portion in the frame is ~~quarried out~~selected and removed, and the moving picture data can be produced.

[0198] Further, in Embodiments 1 to 7, ~~it is described that~~ the moving picture data producing apparatus ~~accommodates~~stores the rate correction data after the normal frame ~~date, however~~data. However, the position ~~to be accommodated,~~where the correction data is stored is not limited to this. For example, when the moving picture data producing apparatus ~~accommodates~~stores the rate correction data after the user data start sign within the moving picture data, the data can be reproduced by using the normal moving picture decoding apparatus.

[0199] Herein, the user data start sign is, for example, as shown in ~~ISO/IEC 11172-2 which is the standard book of MPEG coding~~MPEG coding standard ISO/IEC 11172-2, a sign showing the start of the area which is prepared for the future expansion, and the normal moving picture decoding apparatus skips over the data from the user data start sign to the next start sign and conducts the decoding. Accordingly, the moving picture data produced by the moving picture data producing apparatus in Embodiments 1 to 7, can be reproduced by using the normal moving picture decoding apparatus.

[0200] Further, in the present invention, the input data of the moving picture coding apparatus and output data are compared with each other, or a plurality of output data whose bit rates are different[[,]] are compared, and when. When the bit arrangement is locally different, it is structured in such a manner that the bit arrangement is accommodatedstored in the user data, or a position other than the normal frame data.

[0201] Further, when the monochrome frame is an input, each frame of the moving picture data outputted by the moving picture data producing apparatus has the periodic structure in which, other than normal frame data, as the rate correction data, the entirely same data are periodically included by thefor as many as the number of areas between the areas, and because. Because the entirely the same rate correction data is also included between the frames, the moving picture data has the periodic structure.

[0202] As described above, firstly, when the moving picture data has the structure having the rate correction data whose bit amount is different, to the area in which the bit amount in the P frame (predictive coding image between frames) is large, in the case where the moving picture data is newly produced from the previously coded moving picture data, by selecting the data whose bit amount is different, corresponding to the objective bit rate, the bit rate can be changed without decoding the moving picture data, and the moving picture data can be quickly produced.As described above, first, when new moving picture data is produced from previously coded data, and the new data is structured so

that it includes the rate correction data whose bit amount is different, for the areas in which the bit amount in the P-frame (predictive coding image between frames) is large, by selecting the data whose bit amount is different, corresponding to the desired bit rate, the bit rate can be changed without decoding the moving picture data. Accordingly, the moving picture data can be quickly produced.

[0203] ~~Secondly~~Second, in the case where the moving picture data ~~has~~includes the rate correction data in which the bit amount is different, and the rate change can be conducted, ~~on the predetermined area in which the probability referred to at the time of the motion estimation from the next frame is low~~ in the P-frame (predictive coding image between frames), for the predetermined area in which the likelihood of being referred to from the next frame at the time of the motion estimation is low, and ~~the~~new moving picture data is ~~newly~~ produced from the previously coded moving picture data, by selecting ~~one~~ data from the rate correction data whose bit amount is different, within the input moving picture data, corresponding to the ~~objective~~desired bit rate, the bit rate can be changed without decoding the moving picture data~~, and~~. Accordingly, the moving picture data can be quickly produced. Further, by producing the rate correction data in the area in which the ~~probability~~likelihood of being referred to from the next frame is low, the ~~lowering~~reduction of the predictive coding efficiency due to the influence of the search area limitation of the motion estimation[[,]] can be reduced.

[0204] ~~Thirdly~~Third, in the moving picture data producing apparatus, by providing the motion compensation means for inhibiting the reference, at the time of the motion estimation of the next frame, [[to]]for the area having the rate correction data in the P-frame of the moving picture data to conduct the coding, when the new moving picture data is ~~newly~~ produced from the coded moving picture data, even by selecting the rate correction data whose bit amount is different, corresponding to the objective bit rate, the generation of the motion compensation error due to the change of the data can be prevented.

[0205] ~~Fourthly~~Fourth, in the moving picture data producing apparatus, when the P-frame of the moving picture data is produced, [[to]]for the area in which the referred degree data showing the area in the preceding frame used for reference at the time of motion estimation is recorded, and by using the referred area data, which is selected as the area that the referred degree is low, by providing the means for producing the rate correction data whose bit amount is different, the moving picture coding can be conducted without ~~lowering~~decreasing the coding efficiency of the predictive coding between frames. Further, when [[the]]new moving picture data is ~~newly~~ produced from the previously coded moving picture data, by selecting the data whose bit amount is different, corresponding to the ~~objective~~desired bit rate, the bit rate can be quickly changed without decoding the data~~, and the moving picture data can be produced~~.

[0206] ~~Fifthly~~Fifth, in the moving picture data producing apparatus, by providing the means for producing the data in which the predictive coding

between frames is conducted on the original image to the P-frame of the moving picture data, and the means by which the high frequency component of the original image is removed, and by conducting the predictive coding between frames, the rate correction data whose bit amount is different[[,]] is produced, when. When the new moving picture data is newly produced without decoding the coded moving picture data, by selecting a plurality of areas in the rate correction data, in which the high frequency component is removed and coded, and bit amounts are different, the fine bit rate control can be quickly conducted.

[0207] SixthlySixth, in the moving picture data producing apparatus, by providing the means for producing the position at which the subsequent bit can be deleted, and the termination data to each Video Packetvideo packet of the moving picture data[[,]]; and in the moving picture coding apparatus by which the new moving picture data is produced from the coded moving picture data is produced, by selecting the Video Packet correspondingvideo packet according to the objectivedesired bit rate, and by deleting the rear portion bits, the bit rate control can be quickly conducted.

[0208] Seventhly, inSeventh, when the moving picture data producing apparatus, in the case where includes the means for producing a plurality of I-frames whose bit amounts are different[[,]] as the rate correction data, to the P-frame of the moving picture data, is provided, when theand new moving picture data is newly produced from the previously coded moving picture data, by selecting or frame skipping the rate correction data corresponding to the

objective bit rate, ~~the~~ bit rate control can be quickly conducted, and the moving picture data can be produced.

[0209] ~~Eighthly, in the case where the structure in which an area having together the rate correction data whose bit amount is different in the P frame (predictive coding image between frames) of the moving picture data is provided at least one for each quarry out area determined in the frame is provided, and the moving picture data producing means is provided with the motion compensation means in which the motion estimation is not conducted from the different quarry out area and the area having the rate correction data, when one portion in the frame is quarried out from the previously coded moving picture data and the moving picture data is newly produced, by selecting the data whose bit amount is different, corresponding to the objective bit rate, the bit rate can be controlled without decoding the moving picture data, and without generating the motion compensation error, and the moving picture data can be quickly produced.~~ Eighth, when a current embodiment includes structure wherein at least one area having the rate correction data whose bit amount is different in the P-frame of the moving picture data is provided for each select and remove area (the select and remove area is determined in the frame); and the moving picture data producing means is provided with the motion compensation means in which the motion estimation is not conducted from the different select and remove area and the area having the rate correction data, when one portion in the frame is selected and removed from the previously coded moving picture data and new moving

picture data is produced; by selecting the data whose bit amount is different, corresponding to the desired bit rate, the bit rate can be controlled without decoding the moving picture data, and without generating the motion compensation error, and the moving picture data can be quickly produced.